

G2L92A2U

# G2L92A2U

- Cable set for 4K Dual View DisplayPort USB KVM with Audio (GCS1942NC/GCS1942/GCS1944)
- High Resolution 4096 x 2160 @60Hz
- USB 3.0 Connectivity
- Analog 3.5mm for Speaker and Microphone Support
- TAA Compliant



The Dual View DisplayPort Cable Kit (G2L2A2U) is designed specifically for the IOGEAR 2/4-Port 4K Dual View DisplayPort KVMP Switch (GCS1942NC/GCS1942/GCS1944). This cable set is comprised of (2) 5 ft. DisplayPort cables, (1) 6 ft. USB 3.0 cable and (2) 6 ft. Audio cables.

- Cable set for 4K Dual View DisplayPort USB KVM with Audio (GCS1942NC/GCS1942/GCS1944)
- High Resolution 4096 x 2160 @60Hz

- USB 3.0 Connectivity
- Analog 3.5mm for Speaker and Microphone Support
- TAA Compliant



**Requirements**

Computers with DisplayPort and USB connections

**Package Contents**

- 2 x DisplayPort Cable (5ft)
- 1 x USB cable (6ft)
- 1 x Audio cable set (6ft)

Specifications

Function	G2L92A2U	Dimensions	G2L92A2U
<b>Cable Connections</b>		<b>Unit Package Dimensions</b>	
Input	2 x DisplayPort Male, 1 x USB 3.0 Type-A Male, 2 x Analog 3.5mm Audio	Height	1.5 in. (3.8 cm)
Output	2 x DisplayPort Male, 1 x USB 3.0 Type-B Male, 2 x Analog 3.5mm Audio	Length	10 in. (25.4 cm)
<b>Cable Length</b>	DisplayPort 5ft, USB (6ft), Audio (6ft)	Width	8 in. (20.3 cm)
		<b>Master Carton</b>	
		Height	8 in. (20.3 cm)
		Length	20 in (50.8 cm)
		Width	14 in. (35.6 cm)
		Master Carton Qty.	24
		<b>Weight</b>	
		Master Carton Wt.	20.05 lb. (9.1 kg)
		Unit Wt.	0.8 lb. (0.36 kg)