

G2LU3AB6

## USB 3.0 Type A to Type B Cable- 6.5ft (2m)



### USB 3.0 Type A to Type B Cable

IOGEAR's USB 3.0 Type A to Type B cable is the answer to your USB 3.0 device solution! It allows data transfer rate of up to 5Gbps, provides high quality performance, and supports the needs of your high speed applications. The USB 3.0 Type A to Type B cable connects your USB 3.0 device up to 6.5ft away without the need to install drivers or connect to an external power supply. Backwards compatible with USB 2.0 and USB 1.1 devices, this cable is the perfect solution for USB 3.0 devices, such as USB 3.0 docking stations, USB 3.0 hard drives, printers, and other USB 3.0 peripherals.

IOGEAR's USB 3.0 Type A to Type B cables are designed to connect from a USB port on your Hub, PC or Mac to your USB device. Foil and braid shielding reduces EMI/RFI interference and our twisted-pair construction helps reduce crosstalk to ensure high-speed, error-free data transfer. This cable features the latest design and technology and is backed by IOGEAR's Limited Lifetime Warranty.

The USB 3.0 Type A to B Cable - 6.5ft (2m) serves as an upgrade or replacement of the factory supplied cable included with the [IOGEAR USB 3.0 Universal Docking Station](#).

- Connect a USB 3.0 device up to 6.5ft away
- USB 3.0 transfer rates of up to 5Gbps
- Up to 10x faster than USB 2.0
- Backwards compatible with USB 2.0 and 1.1 devices
- Plug & Play design-no drivers or power supply needed
- Perfect for devices as USB switches, USB docking stations, printers and other USB peripherals
- Compatible with PC and Mac



## Requirements

- **Hardware:**
  - USB 3.0 Type A port
  - USB 3.0 Type A device
  - USB 3.0 Type B port
  - USB 3.0 Type B device
  -
- **Operating System:**
  - Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1
  - Mac OS X+

## Package Contents

- 1 x G2LU3AB6

## Specifications

Function	G2LU3AB6
<b>Cable Length</b>	6.5ft (2m)
<b>Connectors</b>	
Cable	Nickel-plated
<b>Cable Type</b>	Copper conductor, Blue PVC jacket, 28 AWG, OD: 5.5mm
<b>Operating Temperature</b>	20 - 50 degrees (Celsius)
<b>Storage Temperature</b>	0 - 70 degrees (Celsius)
<b>USB Specification</b>	USB 3.0, 2.0 and 1.1 compliant
<b>Transfer Rate</b>	Up to 5Gbps
<b>Humidity</b>	20 - 80% RH, (Non-condensing)
<b>Operating System Support</b>	Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Mac OS X+
<b>Cable Connections</b>	
Input	USB 3.0 Type A
Output	USB 3.0 Type B

Dimensions	G2LU3AB6
<b>POP Information</b>	
10" Peg Hook	14
6" Peg Hook	8
<b>Unit Dimensions</b>	
Height	0.5" (1.27cm)
Depth	0.44" (1.12cm)
Length	6.63ft (201.93cm)
<b>Unit Package Dimensions</b>	
Width	6.69" (16.99cm)
Height	9.38" (23.83cm)
Depth	0.75" (1.91cm)
<b>Master Carton</b>	
Width	19.63" (49.86cm)
Height	7.75" (19.69cm)
Depth	11.75" (28.95cm)
Master Carton Qty.	48
<b>Weight</b>	
Master Carton Wt.	12.07lb (5.48kg)
Unit Pack Wt.	0.22lb (0.099kg)
Unit Wt.	0.19lb (0.087kg)