

G2LVGA006

## Ultra-Hi-Grade VGA Male to Male Cable (6 ft)



IOGEAR's CL3 rated Ultra-Hi-Grade VGA Cables are a necessity for any Systems Integrator working on an educational or commercial installation. VGA cables are used for video projectors, plasma screens, LCD or CRT monitors, and in installations where the cable must perform over long distances. Cable construction ensuring signal integrity in your installation. The cable is double shielded providing a minimum of 85% coverage, by Mylar aluminum foil and drain wire to provide 100% coverage. Don't be misled by cable dealers selling low cost, so-called premium cables that don't meet the minimum requirements, those cables will cost you much more in the end.

- Connectors: HD15 Male to HD15 Male
- CL3 rated
- Constructed from premium grade double-shielded twisted pairs and triple-shielded coax
- Ultra shielded for protection from EMI / RFI interference
- Accommodates cable runs up to 100 ft without a signal booster
- Ideal for video presentation devices, home theatre and HDTV applications, classroom environments, POS, server rooms and more applications



How does it work?



Coaxial Cables for Red, Green and Blue video signals to reduce radio frequency interference

Copper Braid RF shield cables to reduce RF interference even in the most electronically "noisy" environment.

Requirements

- VGA source device with a HD15 Female connection
- VGA display with a HD15 Female connection

Package Contents

1 x 6ft Ultra-Hi-Grade VGA Cable

Specifications

Function	G2LVGA006	Dimensions	G2LVGA006
Cable Length	6 ft	Unit Dimensions	
Connectors	HD15 Male to HD15 Male	Length	6ft
		Inner Pack	
		Inner Pack Qty.	12
		Unit Package Dimensions	
		Width	6.25in.
		Height	8in.
		Depth	1in.
		Master Carton	
		Master Carton Qty.	48
		Weight	
		Unit Wt.	0.5lb