

G2LVGAE050

Ultra-Hi-Grade VGA Extension Cable 50 feet



IOGEAR's rated Ultra-Hi-Grade VGA Extension Cables are a necessity for any Systems Integrator working on an educational or commercial installation. VGA cables are used for video projectors, plasma screens, LCD or CRT monitors, and in installations where the cable must perform over long distances. Cable construction ensuring signal integrity in your installation. The cable is double shielded providing a minimum of 85% coverage, by Mylar aluminum foil and drain wire to provide 100% coverage. Don't be misled by cable dealers selling low cost, so-called premium cables that don't meet the minimum requirements, those cables will cost you much more in the end.

- Connectors: HD15 Male to HD15 Female
- CL3 rated
- Constructed from premium grade double-shielded twisted pairs and triple-shielded coax
- Ultra shielded for protection from EMI / RFI interference
- Accommodates cable runs up to 100 ft without a signal booster
- Ideal for video presentation devices, home theatre and HDTV applications, classroom environments, POS, server rooms and more applications



Requirements

Package Contents

1 x 50ft Ultra-Hi-Grade VGA Extension Cable

Specifications

Function	G2LVGAE050	Dimensions	G2LVGAE050
Cable Length	50 ft	Unit Dimensions	
Connectors	HD15 Male, HD15 Female	Width	8.5 in (22cm)
		Height	3.5 in (9 cm)
		Depth	8.5 in (22cm)
		Unit Package Dimensions	
		Width	8.5 in (22cm)
		Height	3.5 in (9 cm)
		Depth	8.5 in (22cm)
		Master Carton	
		Width	15.5 in (39.37 cm)
		Height	10.5 in (26.67 cm)
		Depth	15.5 in (39.37 cm)
		Master Carton Qty.	10
		Weight	
		Master Carton Wt.	43.0 lbs (19.5 kgs)
		Unit Pack Wt.	3.98 lbs (1.81 kgs)
		Unit Wt.	3.98 lbs (1.81 kgs)