

## GBB1000N

# Professional Online 1000VA, 1000W UPS - TAA



- True double-conversion – Output power factor is 1 (maximum), which means all of the power supplied is being used for productive work and makes work the most efficient.
- Output voltage regulation < 1% – Provides higher performance and efficiency for critical applications.
- Programmable power management outlets – Users can easily and independently control load segments. During power failure, this feature enables users to extend battery time to mission-critical devices by shutting down noncritical devices.
- Emergency Power Off function (EPO) – EPO connector at rear panel allows emergency UPS Power Off from a remote location.
- SNMP + USB + RS-232 multiple communications – Allows either USB or RS-232 communication ports to work with SNMP interface simultaneously.

## Reliable Power Back Up for All Server IT Equipment Needs

IOGEAR Online UPS Battery Back Up GBB1000N – 1000VA/1000 Watts is a high-performance UPS system with NEMA 5-15P input plug and 8 NEMA 5-15R outlets designed for most server rack configurations that support data, network and communication applications. It utilizes true double conversion with up to 100% power factor efficiency for all the power supplied by the UPS for critical IT equipment needs and output voltage regulation provides higher performance for critical applications. The rackmount form factor installs use only two rack spaces (2U). It ships with all mounting accessories for a four-post rackmount installation.

- True double-conversion – Output power factor is 1 (maximum), which means all of the power supplied is being used for productive work and makes work the most efficient.
- Output voltage regulation < 1% – Provides higher performance and efficiency for critical applications.
- Pure sine wave output - Provides clean power source to your sensitive and mission critical equipment, such as IT, Medical, Telcom, to keep the great performance and prevent unexpected shutdown and damage.
- Programmable power management outlets – Users can easily and independently control load segments. During power failure, this feature enables users to extend battery time to mission-critical devices by shutting down noncritical devices.
- Emergency Power Off function (EPO) – EPO connector at rear panel allows emergency UPS Power Off from a remote location.
- SNMP + USB + RS-232 multiple communications – Allows either USB or RS-232 communication ports to work with SNMP interface simultaneously.
- Hot swappable battery design – All potential UPS maintenance, including complete power module exchange, can be performed without powering down connected equipment. As long as utility power is on, you can leave the UPS and connected equipment on while replacing the battery.
- ECO mode for energy saving – Offers up to 97% efficiency to cut energy usage and cost. UPS power application via static bypass, timely returning to online double conversion when the need arises.
- Provides over-voltage cut-off protection and surge immunity by MOV for full-time equipment protection.
- High power factor charger up to 1000W capacity with very low ripple current when charging battery.
- Multi-functional LCD interface – Displays immediate, detailed information on input voltage, battery capacity, power status, battery status, operating status, and assessed backup runtime, etc.
- Smart battery charger design to optimize battery performance – Adjusts charging voltage according to outside temperatures and extends the useful service life of batteries.



Requirements	Package Contents
Source Outlet Type - NEMA 5-15R	<ul style="list-style-type: none"><li>• 1 x Online UPS - GBB1000N</li><li>• 1 x Rack Mounting Kit Set</li><li>• 4 x Tower Stand</li><li>• 1 x Rail Slide Kit Set</li><li>• 1 x RS-232 Cable</li><li>• 1 x USB Type-A to B Cable</li><li>• 1 x User Manual</li></ul>
Device Plug Type- NEMA 5-15P	

## Specifications

Function	GBB1000N	Dimensions	GBB1000N
<b>UPS Topology</b>	On-Line (Double Conversion)	<b>Unit Dimensions</b>	
<b>Energy Saving</b>	>96%(ECO), >89%(AC), >88%(Batt)	Height	3.5 in. (8.9 cm)
<b>Network Interface</b>	SNMP Card	Length	16 in. (40.7 cm)
<b>Input</b>		Width	17.3 in. (44 cm)
Voltage	100/110/115/120V	<b>Master Carton</b>	
Voltage Range	80-150 VAC $\pm$ 5% @ 100% load, 55-150 VAC $\pm$ 5% @ 50% load, Derate capacity to 80% when the output voltage is adjusted to 100VAC	Height	9.5 in. (24.2 cm)
Frequency Range	40 Hz ~ 70 Hz	Length	23.5 in. (59.7 cm)
Cold Start	Yes	Width	19.75 in. (50.2 cm)
Plug Type	NEMA 5-15P	Master Carton Qty.	1
Power Factor	>0.99 @ nominal voltage (100% load)	<b>Weight</b>	
Cord Length	6 ft.	Master Carton Wt.	39.8 lb. (18.1 kg)
<b>Output</b>		Unit Wt.	28.4 lb. (12.9 kg)
Volt Amp Capacity (VA)	1000		
Output Watt Capacity (Watts)	1000		
Rated Power Factor	1		
On Battery Waveform	Sine Wave		
On Battery Frequency	50/60Hz $\pm$ 3 Hz		
Outlets	8x NEMA 5-15R		
Outlet Types - Battery & Surge Protected	8 x NEMA5-15R		
Crest Factor	3:1		
Harmonic Distortion	<5% THDv (Linear Load), <4% THDv (Non-linear Load)		
Voltage Regulation	$\pm$ 1%(Batt)		
Transfer Time (AC to Battery)	0ms		
Transfer Time (Inverter to Bypass)	4ms(ECO)		
<b>Battery</b>			
Runtime at Half Load (min)	10.1		
Runtime at Full Load (min)	2.95		
Battery Type	Sealed Lead-Acid		
Battery Pack Voltage	24V		
Battery Quantity	2		
Hot-Swappable	Yes		
Typical Recharge Time	3 hours recover to 95% capacity @2A charging current., Max charger current 8A		
Extended Battery Module	GBP24V18AH		
<b>Environment</b>			
Operation Temperature	0 $\pm$ 40 $^{\circ}$ C (32 $\pm$ 104 $^{\circ}$ F)		
Storage Temperature	-20 $\pm$ 50 $^{\circ}$ C (-4 $\pm$ 122 $^{\circ}$ F)		
Humidity	20-90% RH / 10% to 95% (no condensing)		
<b>Certification</b>	UL FCC		

at Home at Work on-the-Go

