

GBMA201

Wireless Audio Transmitter



IOGEAR's Bluetooth Audio Transmitter brings wireless Bluetooth technology to all your music and audio devices including iPod, computer, MP3 players, home stereos, TV sets, and more. Designed to work in conjunction with IOGEAR's Bluetooth Stereo Headphones (GBMH201), this wireless audio transmitter plugs into the audio jack of your music devices, and delivers mp3-quality stereo sound to the headphones, wirelessly.

Best of all, there is no software or complicated configuration required. This adapter will essentially work with any audio device that has a standard RCA, phono connector, or 3.5mm audio jack found in most audio devices.

The auto-connect feature allows connection to Bluetooth stereo headphone (GBMH201) in seconds by simply turning on both devices. The built-in rechargeable batteries offer 6.5 hours of continuous operation with each full charge. And the compact and light-weight design makes this adapter unobtrusive and highly portable.

- For use with IOGEAR Bluetooth Stereo Headphones (GBMH201)
- Plugs into any standard 3.5mm, RCA, or phono plug
- Use it on your iPod/iPod Mini, stereo, boom box, computer, MP3 player, and other music devices
- No software required; Plug-n-Play
- Wireless range up to 66 ft (20 meters)
- Built-in rechargeable batteries for up to 6.5 hours of continuous operation
- Very light and portable
- RCA audio cable and Phono plug adapter included
- Class 2 device compliant with Bluetooth 1.2 specifications



Requirements

Compatible with most IOGEAR Bluetooth stereo headphones (GBMH201)

Music/Audio device must have 3.5mm audio connector, phono plug, or RCA audio jacks

Package Contents

- 1 x BluetoothAudio transmitter
- 1 x 3.5mm to RCA audio cable
- 1 x 3.5mm to 1/4" phono plug
- 1 x 3.5mm extension cable
- 1 x Power adapter
- 1 x Quick Start Guide
- 1 x Warranty/Registration card

Specifications

Function	GBMA201	Dimensions	GBMA201
Power Consumption	Inquiry 63mA; Play 81mA; Pause from Sink 67mA	Unit Dimensions	
Frequency Band	2402 - 2480MHz	Height	.4 in.
Modulation	GFSK (Gaussian Frequency Shift Keying)	Length	2 in.
Data Rate	1Mbps	Width	2 in.
Sensitivity	< 0.1% BER @ -78dBm	Unit Package Dimensions	
Security	Pairing, Encryption, and Authentication	Height	3.0 in.
Profiles Supported	A2DP (Advanced Audio Distribution Profile)	Width	7.875 in.
Battery Type	Rechargeable 3.7V Lithium-Polymer 480mAh	Depth	11.375 in.
RF Spreading	RF Output power -3dBm - +2dBm	Master Carton	
Antenna Type	PIFA	Height	12 in.
Range	Maximum 66 ft. (20 meters)	Width	8.5 in.
Audio		Depth	16 in.
Codec	Sub Band Codec	Master Carton Qty.	6
Frequency Response	20Hz - 20KHz	Weight	
International - Languages	English, French, Spanish	Master Carton Wt.	6.10 lbs
		Unit Pack Wt.	1 lbs.
		Unit Wt.	.05 lbs (0.8 oz)