

GCL1808

8-Port 17" LCD Combo KVM Switch (TAA Compliant)



- Integrated 8-port KVM console featuring a 17" TFT LCD active matrix monitor, keyboard and touchpad
- 1280 x 1024 resolution on 17" rack mount LCD provides a sharp video display
- Auto Scan Mode to monitor connected computers
- Broadcast Mode to send commands to all connected computers
- Adjustable depth to fit different sizes of racks

8-Port Combo LCD KVM

IOGEAR's 8-Port 17" LCD Combo KVM Switch integrates a 17" LCD console with an 8-port KVM (keyboard, video, and mouse) switch, offering secure access to 8 VGA, USB or PS/2 computers. This 8-Port LCD KVM features a convenient rack mountable sliding / retractable 17" TFT LCD active matrix monitor and keyboard with built-in touchpad for a space-saving and streamlined integration. For added convenience it also supports an external USB mouse. All this in a universal 1U rack mount space.

- Integrated 8-port KVM console featuring a 17" TFT LCD active matrix monitor, keyboard and touchpad
- 1280 x 1024 resolution on 17" rack mount LCD provides a sharp video display
- Auto Scan Mode to monitor connected computers
- Broadcast Mode to send commands to all connected computers
- Adjustable depth to fit different sizes of racks
- Multi platform OS support - Windows®, Mac, Sun Solaris™ , and Linux®
- Easy to operate - computer selection via front panel pushbutton LED's, intuitive OSD (on screen display), and hotkeys
- Auto Scan Mode to monitor all connected computers
- External USB mouse port for convenience
- External USB or PS/2 with VGA Console port
- Support special keys on Mac and Sun keyboards
- USB media port support for attached USB computers (system upgrades, etc) **
- Cascade up to 2 levels - control up to 128 computers from a single console*
- Security - 2 level password protection for OSD
- DDC Emulation - Video settings of each computer are automatically adjusted for optimal output to the monitor
- Rack mountable in a 19" (1U) system rack
- Firmware upgradeable
- Custom ASIC provides an auto-sensing function that recognizes the position of each station on the installation
- Fully Supports DDC2B

*Cascade with IOGEAR 8/16-Port VGA Combo KVM Switch (Model No. GCS1808 and GCS1716)

**Only systems connected with the USB KVM cables will be able to access the front USB port for system upgrades and shared peripherals





Requirements

Computers:

- VGA, SVGA, or MultiSync video graphics card with an HDB-15 port
- PS/2 mouse and keyboard ports (6-pin mini DIN) or 1 USB port

Operating Systems:

- Windows(R) XP, Windows Vista(R), Windows(R) 7*, Windows(R) 8, Windows(R) 8.1, Windows 10
 - Mac OS 9 to 10.x
 - Oracle(R) Solaris
 - Linux , Unix and other USB supported systems **
- **Additional drivers and support may be needed
 *IOGEAR's DynaSync provides the EDID support for Windows(R) 7

Package Contents

- 1 x 8-Port LCD KVM
- 1 x PS/2 KVM Cable
- 1 x USB KVM Cable
- 1 x Console Cable
- 1 x Cascade Cable
- 1 x Firmware Upgrade Cable
- 1 x Rack Mount Kit - Short Bracket(Fits 16 .6~32.2 Inch Depth) and Long Brackets(Fits 26 .8~41.3 Inch Depth)
- 1 x Grounding Wire
- 1 x Power Cord
- 1 x Installation Guide
- 1 x Warranty Card

Specifications

Function	GCL1808	Dimensions	GCL1808
Computer Connections		Unit Dimensions	
Direct	8	Height	1.75in.
Daisy Chain or Cascading	128	Depth	25in.
Port Selection	OSD, Hotkeys, Pushbuttons	Width	19in.
Connectors		Unit Package Dimensions	
Console	1 x SPHD-18 Male	Height	5.5in.
Power	1 x 3-Prong AC Socket	Width	26.75in.
Console Connectors		Depth	28.5in.
Monitor	1 x HDB-15 Female	Weight	
Keyboard	PS/2 or USB	Unit Pack Wt.	44.03lb
Mouse	PS/2 or USB	Unit Wt. w/accessories	33.07lb
Extra Mouse	1 x USB Type A Female	Unit Wt.	27.78lb
Flash ROM Upgrade	1 x RJ-11 Female		
CPU Connectors			
Keyboard, Mouse, and Monitor	8 x SPHD-15 Female		
Switches			
Reset	1 x Semi-recessed Pushbutton		
Power	1 x Rocker Switch		
F/W Upgrade	1 x Switch		
LCD Adjustment	4 x Pushbutton		
LCD Power	1 x LED Pushbutton (Orange)		
Port Selection	8 x Pushbutton		
LEDs			
On Line	8 (Orange)		
Port ID	4 x 7 Segment LED Display (Yellow)		
Power On	Dark Green		
Emulation			
Keyboard	PS/2, USB		
Mouse	PS/2, USB		
Video Resolution	1280 x 1024 @ 75Hz; DDC2B		
Scan Interval	1-255 Seconds		
Power Input Rating			
Per AC Power Inlet, 50/60Hz	100~240VAC. 50/60Hz, 1A		
Power Consumption	120V, 28W		
Environment			
Operation Temperature	0~40°C		
Storage Temperature	-20~60°C		
Humidity	0~80% RH; Non-condensing		
Housing			
Case	Metal and Plastic		