

GCL1908KITU

## 8-Port 19" LCD KVM Drawer Kit with USB KVM Cables



- Integrated 8-port KVM console featuring a 19" TFT LCD active matrix monitor, keyboard and touchpad
- 1280x1024 resolution on 19" rack mount LCD provides a sharp video display
- Adjustable mounting rail to fit different sizes of racks
- Multiplatform OS support - Windows®, Mac and Linux®
- Easy to operate - computer selection via front panel pushbutton LED's, intuitive OSD (on-screen display) and hotkeys

### 8-Port KVM LCD Console

IOGEAR's GCL1908 is an integrated LCD console with an 8-port KVM (keyboard, video, and mouse) switch that offers secure access to 8 VGA, USB or PS/2 computers. It features a convenient rack mountable sliding / retractable 19" TFT LCD active matrix monitor and keyboard with built-in touchpad for a space-saving and streamlined integration. The GCL1908 fits into a universal 1U rack mount space.


The GCL1908 supports both PS/2 and USB keyboards and mice for the connected computers, and supports USB peripheral devices for the attached computers. A single GCL1908 can control up to 8 computers, but as many as 8 additional compatible KVM switches can be cascaded to reach up to 128 computers\* controlled from a single keyboard, monitor and mouse console.

- Integrated 8-port KVM console featuring a 19" TFT LCD active matrix monitor, keyboard and touchpad
- 1280x1024 resolution on 19" rack mount LCD provides a sharp video display
- Adjustable mounting rail to fit different sizes of racks
- Multiplatform OS support - Windows®, Mac and Linux®
- Easy to operate - computer selection via front panel pushbutton LED's, intuitive OSD (on-screen display) and hotkeys
- External USB or PS/2 with VGA Console port
- Cascade up to 2 levels - control up to 128 computers from a single console\*
- Security - 2 level password protection for OSD
- DDC Emulation - Video settings of each computer are automatically adjusted for optimal output to the monitor
- Rack mountable in a 19" (1U) system rack
- Custom ASIC provides an auto-sensing function that recognizes the position of each station on the installation
- Fully Supports DDC2B

\*Can only be cascaded with other IOGEAR KVMs: [GCS1808](#) or [GCS1716](#) models



### How does it work?



### Requirements

- **Computers:**
- VGA, SVGA, or MultiSync video graphics card with an HDB-15 port
- PS/2 mouse and keyboard ports (6-pin mini DIN) or 1 USB port

### Package Contents

- 1 x 8-Port 19" LCD KVM
- 1 x 6ft PS/2 KVM Cable
- 4 x 6ft USB KVM Cable
- 4 x 10ft USB KVM Cable
- 1 x Firmware Upgrade Cable
- 1 x Standard Long Rack Mount Kit (Fits 27.6~41.3 Inch Depth)
- 1 x Power Cord
- 1 x Quick Start Guide
- 1 x Warranty Card

## Specifications

### Function

GCL1908KITU

### Dimensions

GCL1908KITU

#### Unit Dimensions

Height	27" (68.58cm)
Length	17.75" (45.1cm)
Depth	1.75" (4.45cm)

#### Unit Package Dimensions

Height	32.5" (82.55cm)
Width	26.75" (67.95cm)
Depth	5.25" (13.34cm)

#### Master Carton

Height	32.5" (82.55cm)
Width	26.75" (67.95cm)
Depth	5.25" (13.34cm)

#### Weight

Master Carton Wt.	40.85lbs (18.54kg)
Unit Pack Wt.	40.85lbs (18.54kg)
Unit Wt. w/accessories	31.75lbs (14.4kg)
Unit Wt.	27.75lbs (12.58kg)