

GCS1108KIT2

8-Port DVI KVMP Switch with VGA support and Cables



8-Port DVI & VGA KVMP Switch - Cables Included

IOGEAR's 8-port USB DVI VGA KVMP Switch allows access and control of up to 8 computers from a single USB keyboard, USB mouse, and either a DVI or VGA monitor console. Experience video resolution up to 1920 x 1600 with the freedom of choosing either DVI or VGA interface with a complete mix set of both VGA and DVI KVM Cables.


Expanded Connectivity

Control a connection of up to 512 computers by cascading 3 levels of this 8-Port USB DVI & VGA KVMP from a set of console. The built-in USB 2.0 hub allows peripheral sharing between the connected system, backwards compatible with USB 1.1.

- One USB console controls eight DVI or VGA computers
- Supports both digital (DVI), analog (DVI) video and analog (VGA)
- Superior video quality: 1920x1200 (Single Link DVI), 2048x1536 (VGA); DDC2
- Supports widescreen resolutions
- Multiplatform support – Windows, Linux, Mac, Sun
- Computer selection via front panel pushbuttons, hotkeys, and on-screen display (OSD)
- Includes two USB 2.0 peripheral sharing ports
- Independent switching of KVM and USB focus
- Two-level (Administrator / User) password authorization for enhanced security protection
- Cascadable to three levels – control up to 512 computers
- IOGEAR's DynaSync* technology reads and remembers the monitor's parameters (EDID) so there is no delay or change of video resolution when switching between, or booting computers
- Audio enabled – Full bass response provides a rich experience for 2.1 channel surround sound systems
- Complete keyboard emulation for error-free booting
- Console mouse port emulation / bypass feature supports most mouse drivers and multifunction mice
- Mac / Sun keyboard support and emulation**
- Auto Scan Mode for monitoring all computers
- Broadcast mode – allows you to send commands from the console to all computers to perform operations simultaneously
- Firmware upgradable
- HDCP compatible
- Console audio ports on front panel for easy access

*IOGEAR's DynaSync provides the EDID support for Windows 7

**Note: PC keyboard combinations emulate Mac / Sun keyboards; does not emulate Mac / Sun keyboard to PC keyboard



Requirements

Console

- Display Option #1 – A display with both DVI and VGA connection*
- Display Option #2 – A display with DVI-I connection
- Display Option #3 – One each of DVI and VGA displays
- 1 set of USB keyboard and mouse

Computers

- 1 DVI port
- or 1 VGA port
- 1 USB port

Operating Systems

- Windows® 7, Windows® 8, Windows® 8.1, Windows® 10
- Mac OS9 to 10.x
- Sun Solaris
- Linux

*IOGEAR's Display Emulation Technology provides the EDID support for Windows 7

Package Contents

- 1 x GCS1108 8-port USB DVI KVMP Switch
- 4 x 6ft Single Link DVI-D USB KVM Cable
- 4 x 6ft VGA USB Audio / Mic KVM Cable
- 4 x DVI-A (M) to VGA (F) Adapter
- 1 x Firmware Upgrade Cable
- 1 x Power Adapter
- 1 x Foot Pad Set (4 pcs)
- 1 x User Manual
- 1 x Rack Mounting Kit

Specifications

Function	GCS1108KIT2	Dimensions	GCS1108KIT2
CPU Connectors		Unit Package Dimensions	
Monitor	8 x DVI-I ports (female)	Height	10"
Microphone	8 x Microphone jack	Depth	9"
Audio	8 x Stereo earphone jack	Length	22"
Keyboard & Mouse	8 x USB Type B sockets	Master Carton	
Console Connectors		Width	10"
Mouse	1 x USB Type A socket	Height	10"
Keyboard	1 x USB Type A socket	Depth	22"
Monitor	1 x VGA port (female) / 1 x DVI-I port (female)	Master Carton Qty.	1
Microphone	2 x Microphone jack (1 x front panel, 1 x rear panel)	Weight	
Audio	2 x Stereo earphone jack (1 x front panel, 1 x rear panel)	Master Carton Wt.	15.24lbs
LEDs			
Selected	8 x Orange		
On Line	8 x Orange		
USB Peripherals	8 x Green		
Power On	1 x Dark Green		
Port Selection		Front Panel Switches; Hotkey	
Video Resolution		DVI: 1920 x 1200; VGA: 2048 x 1536	
Scan Interval		1-255 secs (Default: 5 secs)	
Emulation			
Keyboard	USB		
Mouse	USB		
Computer Connections			
Direct	8		
Daisy Chain or Cascading	Up to 512 (via Cascade)		
Operating Temperature		0 - 50 C	
Storage Temperature		-20 - 60 C	
Humidity		0 - 80% RH	
Peripheral Sharing		2 x USB 2.0	
Housing			
Case	Metal		