

GCS1204DPKIT

4-Port Dual-Link DVI and DisplayPort KVMP Kit with 2.1 Audio (TAA Compliant)



- Switch between 4 computers with the push of a button
- Offers the flexibility to mix and match computer connections: DVI and DisplayPort
- Kit includes 4 x DisplayPort to DVI Active adapters(GDPDVI4KA)
- · Switching via pushbutton, hotkey, or mouse
- · Save Cabling Costs: All cables are included

4-Port Dual-Link DVI and DisplayPort KVMP with 2.1 Audio

IOGEAR's 4-port Dual-Link DVI and DisplayPort KVMP switch with 2.1 audio offers complete flexibility with your Dual-Link DVI and DisplayPort connections. Take full advantage of the included active DisplayPort adapters. Control and switch between DisplayPort and Dual-Link DVI computers. Take control of four computers and share multiple USB peripherals from a single keyboard, monitor, and mouse console.

- Switch between 4 computers using a single keyboard, mouse, and monitor
- Mix and match between Dual-Link DVI and DisplayPort computer sources
- DynaSync[™] Reads and remembers the monitor's parameters to eliminate delay or change of video resolution when switching between, or booting computers¹
- Compatible with gaming keyboards
- Supports high-end 3D graphics
- · Maximum video resolutions:
 - 4K UHD: 3840x2160 @30Hz (depends on source and compatible monitors)²
 - o DVI-D Dual link: 2560 x 1600
 - o DVI-D Single link: 1920 x 1200
- 2.1 audio support

- Built-in USB 2.0 hub share USB peripherals between all connected computers
- Asynchronous hotkey switching between KVM focus, USB peripheral, and audio ports
- Complete keyboard and mouse emulation for error free booting and real-time switching
- Mouse emulation may be disabled to allow programmable buttons to function
- · Supports Mac keyboard and special keys
- · All cables are included
- Firmware upgradable


¹IOGEAR's DynaSync provides the EDID support for Windows 7 OS ²May be used with IOGEAR's 4K cable <u>GHDDVIC4K3</u>, 4K sources, and 4K monitor











Requirements

Console:

- DVI Monitor
- Standard 104 key wired USB keyboard
- Standard 2 or 3 button USB mouse

Computers:

- DVI or DisplayPort port
- USB Type-A port

Operating Systems:

- Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10
- Mac OS 9 to 10.x
- Oracle® Solaris
- Linux®, Unix and other USB supported systems*

*Additional drivers and support may be needed **IOGEAR's DynaSync provides the EDID support for Windows® 7

Package Contents

- 1 x 4-Port Dual-Link DVI KVMP with 2.1 Audio(GCS1204G)
- 4 x Active DisplayPort to DVI Adapters (GDPDVI4KA)
- 4 x 6ft Custom KVM Cables
- 1 x Power Adapter
- 1 x User Manual
- 1 x Warranty



Specifications

| Function | GCS1204DPKIT | Dimensions | GCS1204DPKIT |
|-----------------------|---|-------------------------|------------------|
| Computer Connections | | Unit Dimensions | |
| Direct | 4 | Height | 10.2" (26cm) |
| Port Selection | Hotkey, Push Button, or 3-button Mouse | Depth | 1.6" (4.1cm) |
| Console Connectors | | Length | 2.9" (7.4cm) |
| Monitor | 1 x Dual Link DVI-I Female | Unit Package Dimensions | |
| Keyboard | 1 x USB Type A Female | Width | 12.9" (32.8cm) |
| Mouse | 1 x USB Type A Female | Height | 8.4" (21.3cm) |
| Audio | 1 x 3.5mm Stereo Jack (Green) | Depth | 4.0" (10.2cm) |
| Microphone | 1 x 3.4mm Stereo Jack (Pink) | Master Carton | |
| CPU Connectors | | Width | 13.7" (32.8cm) |
| Monitor | 4 x Dual Link DVI or DisplayPort Female | Height | 9.4" (23.9cm) |
| Keyboard & Mouse | 4 x USB Type B Female | Depth | 12.9" (32.8cm) |
| Microphone | 4 x 3.4mm Stereo Jack (Pink) | Master Carton Qty. | 3 |
| Audio | 4 x 3.5mm Stereo Jack (Green) | Weight | |
| Peripheral Sharing | 2 x USB 2.0 Type A Female | Master Carton Wt. | 23.6lb (10.73kg) |
| LEDs | | Unit Pack Wt. | 7.4lb (3.36kg) |
| On Line | Dim Orange | Unit Wt. | 2.0lb (0.9kg) |
| KVM | Bright Orange | | |
| USB Peripherals | Green | | |
| Emulation | | | |
| Keyboard | USB | | |
| Mouse | USB | | |
| Video Resolution | 4K UHD: 3840 x 2160 @30Hz (use with GHDDVIC4K3, 4K sources, and 4K monitors); DVI-D: 2560x1600 @60Hz (Dual Link); 1920x1200 @60Hz (Single Link); 3840x2160 @30Hz (4K monitor and source); DVI-A: 2048x1536; DDC2B | | |
| Scan Interval | 1-99 sec (5 sec default) | | |
| Power | | | |
| Voltage | DC 5.3V | | |
| Amps | 2.4A | | |
| Environment | | | |
| Operation Temperature | 0~50?C | | |
| Storage Temperature | -20~60?C | | |
| Humidity | 0~80% RH, Non-condensing | | |
| Housing | | | |
| Case | Metal | | |