

GCS1214TAA4

## 4-Port Single View DVI Secure KVM Switch w/Audio



- **NIAP-Certified PP4.0**  
Validated to Protection Profile for Peripheral Sharing Device v4.0
- **4-Port Single View DVI Secure KVM Switch**  
One USB console controls 4 secure computers on 1 display
- **Superior DVI Dual Link Video Resolution**

DVI Dual Link Resolution: 2560 x 1600 @60Hz

- **Port Selection via Push-Button and Remote Port Selector\*\* for Enhanced Security**  
Keyboard restrictions - OSD & hotkey methods are not allowed
- **Isolated Channel per Port**  
Unidirectional data flow restricts data leakage between connected computers
- **Active Chassis Intrusion Detection**  
Compromising the unit's cover renders the switch inoperable
- **Tamper-Evident Seals**  
Visually detect attempts to gain access to switch's internal components
- **Tamper-Proof Hardware**  
Integrated circuits are soldered directly onto the circuit board to hinder component sabotage
- **Non-Reprogrammable Firmware**  
Prevents tampering and attempts to reprogram the switch's firmware
- **Clears Keyboard Buffer**  
Data clears automatically after transmission to switch and resets
- **Analog Speaker Support**
- Secure audio data input does not convert digital audio to analog audio
- **Multiplatform Support**  
Windows® 2000, Vista, 7, 8, 8.1, 10, 11 Linux, Mac OS X, & Sun
- **Rugged Metal Enclosure**  
Durable, Full Metal Chassis
- **Build-In, Internal Power Supply**

\*\* Remote Port Selector sold separately

### 4-Port Single View DVI Secure KVM with Audio Protection Profile v4.0

Secure and manage multiple data-sensitive systems from one workstation from internal and external cybersecurity threats with the TAA-compliant IOGEAR 4-Port Single View DVI Secure KVM with Audio Protection Profile v4.0. Enable authorized users secure access to up to four systems with one keyboard, mouse, up to two monitors at 2560x1600 @60Hz resolution.

Featuring the latest in Common Criteria and NIAP Protection Profile v4.0 security requirements set for the U.S. government for peripheral sharing switches, the secure KVM switches are built for multiple interfaces and ideal for use in high-security environments that demand rigorous cybersecurity provisions including military and defense, federal agencies, government, utilities, commercial and healthcare applications.

- **NIAP-Certified PP4.0**  
Validated to Protection Profile for Peripheral Sharing Device v4.0
- **4-Port Single View DVI Secure KVM Switch**  
One USB console controls 4 secure computers on 1 display
- **Superior DVI Dual Link Video Resolution**
- **Tamper-Evident Seals**  
Visually detect attempts to gain access to switch's internal components
- **Tamper-Proof Hardware**  
Integrated circuits are soldered directly onto the circuit board to hinder component sabotage

- Port Selection via Push-Button and Remote Port Selector\*\* for Enhanced Security  
Keyboard restrictions - OSD & hotkey methods are not allowed
- Isolated Channel per Port  
Unidirectional data flow restricts data leakage between connected computers
- Active Chassis Intrusion Detection  
Compromising the unit's cover renders the switch inoperable

- Prevents tampering and attempts to reprogram the switch's firmware
- Clears Keyboard Buffer  
Data clears automatically after transmission to switch and resets
- Analog Speaker Support
- Secure audio data input does not convert digital audio to analog audio
- Multiplatform Support  
Windows® 2000, Vista, 7, 8, 8.1, 10, 11 Linux, Mac OS X, & Sun
- Rugged Metal Enclosure  
Durable, Full Metal Chassis
- Build-In, Internal Power Supply

\*\* Remote Port Selector sold separately



## Requirements

## Package Contents

### Console

- DVI monitor capable of the highest resolution that you will be using on any computer in the installation
- Standard 104-key wired USB keyboard
- Standard 2 or 3 button wired USB mouse
- Speaker (optional)

- 1x GCS1214TAA4
- 1x Power Cord
- 1x User Guide
- 1x Warranty Card

### Computers

- 1 x DVI Video output connectors
- A USB Type A port for keyboard and mouse
- A 3.5mm jack Audio port for speaker (Optional)

### Operating Systems

- Win 7, 8, 10, 11
- Linux: Kernel 2.6+, RedHat v6.0+, SuSE v8.2+  
Mandriva(Mandrake) v9.0+
- Unix: AIX v4.3, FreeBSD v3.51+, Sun Solaris v9.0+
- Novell Netware v5.0+Mac OS v9+
- DOS v6.2+

## Specifications

Function	GCS1214TAA4
<b>Computer Connections</b>	
Direct	4
<b>Port Selection</b>	Pushbutton or Remote Port Selector
<b>Console Connectors</b>	
Monitor	1 x DVI-I Dual Link Female(White)
Keyboard	1 x USB Type-A Female (Black)
Mouse	1 x USB Type-A Female (Black)
Audio	1 x Mini Stereo 3.5mm Jack Female (Green)
<b>CPU Connectors</b>	
Monitor	4 x DVI-I Dual Link Female (White)
Keyboard & Mouse	4 x USB Type-B Female (White)
Audio	4 x Mini Stereo 3.5mm Jack Female (Green)
<b>Switches</b>	
Port Selection	4 x Pushbuttons
Power	1 x Rocker
<b>LEDs</b>	
On Line	4 x Orange
Selected	4 x Orange
Power On	1 x Green
Key Lock	3 x Green (Num Lock, Caps Lock, Scroll Lock)
Console Video	1 x Green (Rear Panel)
<b>Emulation</b>	
Keyboard	USB
Mouse	USB
<b>Video Resolution</b>	Up to 2560 x 1600
<b>Power</b>	
Amps	1A
Voltage	100 ~240V, 50 ~ 60 Hz
<b>Environment</b>	
Operation Temperature	0 - 50C
Storage Temperature	-20 - 60C
Humidity	0 - 80% RH, Non-condensing
<b>Housing</b>	
Case	Metal

Dimensions	GCS1214TAA4
<b>Unit Package Dimensions</b>	
Height	4.75 in (12 cm)
Length	16.5 in. (41.9 cm)
Width	8.25 in. (21 cm)
<b>Master Carton</b>	
Height	9.25 in. (23.5 cm)
Length	15 in. (38.1 cm)
Width	17 in. (43.2 cm)
Master Carton Qty.	3
<b>Weight</b>	
Master Carton Wt.	16.9 lb. (7.7 kg)
Unit Pack Wt.	5.15 lb. (2.3 kg)