

GCS138

8-Port MiniView™ Ultra KVM Switch



Your business is growing faster than you expected and four computers simply aren't enough to meet your needs? Not a problem. IOGEAR's new 8-port MiniView? Ultra is just the tool you need to help reduce the need for redundant hardware. Eight monitors, mice and keyboards are simply too expensive, bulky and downright inconvenient for most system administrators. Why bother when you can control all eight, or even up to 512 computers with a single keyboard, monitor and mouse. Just think of the time, space and money you'll save.

But our MiniView? Ultra is much more than a simple 8-port KVM switch. Built-in AutoScan mode lets you conveniently monitor every attached computer for a specified amount of time, while our On Screen Display technology allows you to assign a unique name to each computer and access it via a slick, menu-driven interface. With its 1U, 19" rack-mountable casing and status-monitoring LEDs, the MiniView? Ultra is the perfect switch for your server room or any other multi-computer environment.

- Use one keyboard, monitor and mouse to control 8 computers
- Control up to 512 computers by connecting multiple GCS138s together
- On Screen Display provides a convenient method for accessing the computers
- Slashes costs and space consumed by redundant keyboards, monitors, and mice
- Connected computers can be added or removed from the setup without disturbing the other computers
- Keyboard/mouse translation allows PS/2 peripherals to control both PS/2 and serial-based computers
- Plug-n-Play monitor support. High-resolution video support (up to 1920 x 1440)
- · Easy to install no software required
- Built in AutoScan mode
- · LEDs allow for easy status monitoring
- · Lifetime technical support
- 3 Year Limited Warranty









Requirements

- Computers with PS/2 or serial mouse* connections, PS/2 or AT keyboard** connections, and HDDB15 VGA connection
- *Additional serial to PS/2 adapter required **Additional AT to PS/2 adapter required

Package Contents

- 1 x GCS138 MiniView Ultra™ KVM switch
- 1 x Power adapter
- 1 x Rack mount kit
- 1 x Manual
- 1 x Warranty



Specifications

Function	GCS138	Dimensions	GCS138
Housing		Unit Dimensions	
Case	Metal	Height	1.75 in. (4.45 cm.)
CPU Connectors		Depth	6 in. (15.24 cm.)
Mouse	8x6 pin mini-DIN Female (PS/2)	Width	17 in. (43.18 cm.)
Keyboard	8x6 pin mini-DIN Female (PS/2)	Unit Package Dimensions	
Monitor	8xHDDB15 Male	Height	5.5 in. (13.97 cm.)
Console Connectors		Width	22 in. (55.88 cm.)
Mouse	1x6 pin mini-DIN Female (PS/2)	Depth	9.5 in. (24.13 cm.)
Keyboard	1x6 pin mini-DIN Female (PS/2)	Master Carton	
Monitor	1xHDDB15 Female	Height	10.5 in. (26.67 cm.)
Power		Width	18.25 in. (46.355 cm.)
Voltage	DC 9V	Depth	22.5 in. (57.15 cm.)
Amps	3 00 mA(Max)	Master Carton Qty.	3
LEDs		Weight	
Power On	1	Master Carton Wt.	27.75 lbs. (12.49 kg.)
Selected	8	Unit Pack Wt.	8.4 lbs. (3.78 kg.)
On Line	8	Unit Wt.	7.8 lbs. (3.51 kg.)
Port Selection	Push Buttons, Hot Keys, or OSD		
Power Consumption	400 mA(Max)		
Video Resolution	1920x1440; DDC2B		
Scan Interval	3, 5, 10, 15, 20, 30, 40, 60 seconds		
Emulation			
Keyboard	PS/2, AT		
Mouse	PS/2, Serial		
Computer Connections			
Direct	8		
Daisy Chain or Cascading	512		
Power Adaptor Part #			
for North America	# 0AD8-0009-12BG		