

GCS1732

2-Port MiniView™ Extreme Multimedia KVMP Switch w/Cables



2-Port VGA KVMP Switch with USB & PS/2 Interface and Audio

IOGEAR's MiniView™ Extreme Multimedia KVM and Peripheral Sharing Switch brings extra value to conventional KVM switches by offering USB peripheral sharing capabilities, audio and microphone support, and multi-platform support for Windows®, Mac, and Sun systems using either USB and PS/2 (additional cables needed for PS/2, IOGEAR Part No. [G2L5302P](#)). Save money and reduce clutter by eliminating the need for multiple monitors, keyboards, mice, and peripheral devices such as printers, scanners, external hard drives, and more. Up to 127 different USB devices can be daisy chained from this KVMP switch. Sharing speakers and a microphone also offers extra value and convenience for the users.

USB and KVM technology together makes cross-platform management easy. A single USB console can control a PC and a Mac, or even a Sun workstation, and share peripherals and audio devices between the computers. Any USB-enabled computers, using any USB-compatible operating system, can benefit from the efficiency, expense reduction and convenience of IOGEAR's MiniView™ Extreme KVMP switch.

This 2-port KVM also offers a cost effective solution to increase security by allowing users to switch between the Internet connected PC and an Intranet connected PC.

- Control two USB or PS/2* computers from 1 keyboard, monitor, and mouse
- Increase security for your intranet by separating a PC connected to the Internet and a PC connected to an Intranet
- Share two USB peripheral devices such as printers and scanners, as well as speakers and a microphone*
- High Resolution: Up to 2048 x 1536
- Multi OS platform support
- Computer switching via front panel pushbuttons or hotkeys
- Asynchronous hotkey switching between KVM focus, USB peripheral, and Audio ports
- Complete keyboard and mouse emulation for error free booting
- Support special keys on Mac and Sun keyboard
- LED display for easy status monitoring
- Easy installation: no software required, hot swappable
- Firmware Upgradable

*PS/2 KVM Cables are available and sold separately.



Requirements

- **Console:**
 - 1 x VGA Display
 - 1 x standard 104 key wired USB keyboard
 - 1 x standard 2 or 3 button wired USB mouse
- **Computers:**
 - 1 x VGA Port
 - 1 x USB Port*
 - Audio / Mic Port
- **Operating Systems:**
 - Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10
 - Mac OS 9 to 10.x
 - Oracle® Solaris
 - Linux®, Unix and other USB supported systems*

Package Contents

- 1 MiniView™ Extreme Multimedia KVMP switch
- 2 USB KVM Bonded Cables
- 1 User Manual
- 1 Warranty Card
- 1 Power Adapter
- 1 Firmware Upgrade Cable

*Additional drivers and support may be needed.

**PS/2 KVM Cables are available and sold separately.

***Does not support display emulation for Windows 7 (EDID).

Specifications

Function	GCS1732	Dimensions	GCS1732
Housing		Unit Dimensions	
Case	Plastic/Metal	Height	1.7 in. (4.318 cm.)
Console Connectors		Depth	3.5 in. (8.89 cm.)
Mouse	1 x USB Type A	Width	5.2 in. (13.21 cm.)
Keyboard	1 x USB Type A	Unit Package Dimensions	
Monitor	1 x HDB-15 Female (Std. VGA/SVGA)	Height	11.25 in. (28.575 cm.)
Audio	1 x stereo speaker; 1 x Microphone	Width	3.5 in.
Flash ROM Upgrade	1 x RJ11 socket	Depth	4.25 in. (10.795 cm.)
Power		Master Carton	
Voltage	DC 5V	Height	11.5 in. (29.21 cm.)
Amps	2.6 AMP	Width	13.25 in. (33.66 cm.)
LEDs		Depth	18.50 in. (46.99 cm.)
Selected	2	Master Carton Qty.	6
On Line	2	Weight	
USB Peripherals	2	Master Carton Wt.	21.5 lbs. (9.67 kg.)
Port Selection		Unit Pack Wt.	3.5 lbs. (1.58 kg.)
Push button, Hot Keys		Unit Wt.	0.75 Lb. (0.34 kg.)
Power Consumption			
Bus powered, power adapter for additional power			
Video Resolution			
2048x1536 (Max.); DDC/ DDC2B/ DDC2AB			
Scan Interval			
5 sec.			
Emulation			
Keyboard	USB Plug-n-Play		
Mouse	USB Plug-n-Play		
Computer Connections			
Direct	2		
CPU Connectors			
Audio	2 x stereo speaker; 2 x Microphone		
Peripherals	2 x USB Type A		
Keyboard, Mouse, and Monitor	2 x SPDB15		
Operating Temperature			
4 - 40 C			
Storage Temperature			
-20 - 60 C			
Humidity			
0 - 80% RH			
Cable Length			
2 ea 6 ft (1.8M)			
Peripheral Sharing			
USB, selected through Hotkeys			
Power Adaptor Part #			
for North America	# 0AD8-0005-261G		
for Continental Europe	# 0AD6-1005-261G		
for UK	# 0AD4-3005-261G		