

GCS1772

## Miniview Symphony Multi-function KVM Switch with cables



- Multi-function USB KVM switch integrates a USB 2.0 hub, Ethernet switch, and audio
- Controls two computers with a single VGA monitor, USB keyboard and mouse
- Supports most wireless keyboards and mice
- Built-in USB 2.0 peripheral sharing to share printers, scanners, portable hard drives, etc., with data transfer rates of up to 480 Mbps.
- Built-in 3 port 10/100 Mbps Ethernet switch allows you to easily network and share internet with your computers
- Share one set of speakers with all your computers
- Independent switching of KVM, USB peripherals, and audio focus
- Port selection via Hotkeys and front push-buttons
- Auto scan mode for monitoring all computers
- Power on detection ? automatically switches to the first powered on port
- Superior video quality - up to 2048 x 1536
- Firmware upgradeable
- Easy installation ? no software required
- Keyboard and mouse emulation for error-free boot up
- Hot pluggable ? add or remove computers without powering down the switch
- Compatible with multiple operating platforms (PC, Mac, and Sun)
- Two 6 ft (1.8m) cables included



## Requirements

## Package Contents

### CONSOLE

- VGA or SVGA monitor
- USB style mouse
- USB style keyboard

- 1 x GCS1772 KVM Switch
- 2 x Custom 3.9' (1.8m) KVM cables
- 1 x Firmware upgrade cable
- 1 x Power adapter
- 1 x User manual
- 1 x Quick start guide

### COMPUTER

- 1 x VGA or SVGA port
- 2 x Type A USB port (USB 2.0 required for high speed capability)
- Audio ports (optional)
- Windows 98, 98SE, ME, 2000, XP, Vista, VISTA
- Mac OS 8.6 or greater
- Linux, UNIX and other USB supported systems\*

\*Additional drivers and support may be needed

### CABLES:

- Only IOGEAR Custom cable sets specifically designed to work with this switch may be used to link to the computers. Four cable sets are provided with this package.

### AUDIO

- Requires 2-piece powered speaker system

## Specifications

Function	GCS1772	Dimensions	GCS1772
<b>Housing</b>		<b>Unit Dimensions</b>	
Case	Metal	Width	3.5 in (8.89 cm)
<b>CPU Connectors</b>		Height	2.19 in (5.56 cm)
Mouse	USB	Length	8.27 in (21 cm)
Keyboard	USB	<b>Unit Package Dimensions</b>	
Monitor	HDB-15	Width	8.78 in (22.3 cm)
Peripherals	USB 2.0 port	Height	3.86 in (9.8 cm)
<b>Console Connectors</b>		Length	10.55 in (26.8 cm)
Mouse	1 x USB Type A female	<b>Master Carton</b>	
Keyboard	1 x USB Type A female	Width	11.22 in (28.5 cm)
Monitor	1 x HDB-15 female	Height	9.53 in (24.2 cm)
Audio	1 x speaker; 1 x mic	Depth	12.40 in (31.5 cm)
Flash ROM Upgrade	1 x RJ-11	Master Carton Qty.	3
<b>Power</b>		<b>Weight</b>	
Voltage	1 x DC 5.3V; 2.4A	Master Carton Wt.	13.45 lbs (6.123 kg)
<b>Port Selection</b>	Hotkeys or Front Panel switches	Unit Pack Wt.	3.75 lbs (1.7 kg)
<b>Power Consumption</b>	DC 5.3V; 4.5W; 900mA	Unit Wt.	1.56 lbs (0.707 kg)
<b>Scan Interval</b>	1-99 secs (5 sec default)		
<b>Computer Connections</b>			
Direct	2		
<b>Operating Temperature</b>	0-50 Celsius		
<b>Storage Temperature</b>	-20-60 Celsius		
<b>Humidity</b>	0-80% RH		
<b>Cable Length</b>	2 ea @ 3.9ft (1.2M)		
<b>LAN Connection</b>	10/100 Mbps		
<b>LEDs</b>			
Link	3 (green)		
USB Peripherals	2 (green)		
LAN	3 (green)		
<b>Resolution</b>	2048 x 1536		