

GCS1804MDPKIT

4-Port VGA and Mini DisplayPort KVM Switch Kit with Audio and OSD




- Switch between four computers with the push of a button
- Offers the flexibility to mix and match computer connections: VGA and DisplayPort
- Includes 2 x DisplayPort to VGA adapters
- Switching via pushbutton, hotkey, or OSD
- Save Cabling Costs: ALL cables are included

4-Port VGA / Mini DisplayPort KVM Switch

- Switch between four computers with the push of a button
 - Offers the flexibility to mix and match computer connections: VGA and Mini DisplayPort
 - Includes 2 x Mini DisplayPort to VGA adapters
 - Switching via pushbutton, hotkey, or OSD
 - Cost effective, Plug-N-Play solution
- Switch between four computers with the push of a button
 - Offers the flexibility to mix and match computer connections: VGA and Mini DisplayPort
 - Includes 2 x Mini DisplayPort to VGA adapters
 - Switching via pushbutton, hotkey, or OSD
 - Cost effective, Plug-N-Play solution
 - 4-port KVM switch with OSD and built-in 2-port High Speed USB 2.0 hub
 - Dual interface - Supports computers with PS/2 or USB keyboard and mouse configurations**
 - Audio enabled - Full bass response provides 2.1 stereo sound
 - Console audio ports on front panel for easy access
 - Independent (Asynchronous) Hotkey switching between KVM focus, USB peripherals, and audio ports
 - Three convenient computer switching methods - front panel pushbutton, On Screen Display (OSD), or Hotkeys
 - Maximum VGA video resolution 2048 x 1536 - supports widescreen monitors
 - IOGEAR's DynaSync reads and remembers the monitor's parameters (EDID) so the user doesn't experience delays or change in video resolution when switching between or booting computers*
- Console mouse port emulation bypass feature supports programmable mice
 - Complete keyboard emulation for error free booting
 - Sun/Mac keyboard support and emulation***
 - Complete solution – All cables included
 - Converts your Mini DisplayPort to VGA
 - Works with Apple® iMac® or MacBook®
 - Compliant with Mini DisplayPort Specification 1.1a for both 1.62 Gbps and 2.7 Gbps
 - Support full Mini DisplayPort link tracking
 - Supported resolutions:
 - Full HD 1080p
 - 1920x1200
 - VGA, SVGA, XGA, SXGA and UXGA at 162 MHz pixel rate
 - Support interrupt request output for expansion function
 - Support Deep Sleep Mode (suspend mode)
- *IOGEAR's DynaSync provides the EDID support for Windows 7
 **PS/2 KVM Cables are available and sold separately.
 *** PC keyboard combinations emulate Sun/Mac keyboards and Sun keyboards only work with Sun computers





Requirements

Package Contents

- | | |
|---|---|
| <ul style="list-style-type: none"> • Console: • Monitor with VGA capabilities • Standard 104 key wired USB or PS/2 keyboard • Standard 2 or 3 button wired USB or PS/2 mouse • • Computers: • VGA or Mini DisplayPort port • USB or PS/2 connections • • Operating Systems: • Windows Vista®, Windows® 7, Windows® 8.1, Windows® 10 • Mac OS 9 to 10.x • Oracle® Solaris • Linux®, Unix and other USB supported systems** • • Optional: • Computers with sound support • 2.0 or 2.1 powered PC speakers • Microphone | <ul style="list-style-type: none"> • 1 x 4-Port USB KVMP Switch • 2 x Mini DisplayPort to VGA Adapters • 4 x Custom USB KVM Cable • 1 x PS/2 to USB Adapter • 1 x Firmware Upgrade Cable • 1 x Power Adapter • 1 x Installation Guide • 1 x Warranty Card |
|---|---|

*IOGEAR's Display Emulation Technology provides the EDID support for Windows 7

**Additional drivers and support may be needed

Specifications

Function	GCS1804MDPKIT	Dimensions	GCS1804MDPKIT
Computer Connections		Unit Dimensions	
Direct	4	Height	7.9" (20.1cm)
CPU Connectors		Depth	1.6" (4.1cm)
Monitor	4 x VGA; 2 x Mini DisplayPort (with adapters)	Length	2.9" (7.4cm)
Keyboard	4 x USB or PS/2	Unit Package Dimensions	
Mouse	4 x USB or PS/2	Width	12.9" (32.8cm)
Microphone	Standard	Height	8.4" (21.3cm)
Audio	2.1	Depth	4.0" (10.2cm)
Peripherals	2 x USB 2.0	Master Carton	
Console Connectors		Width	17.5" (44.4cm)
Monitor	VGA	Height	13.8" (35.0cm)
Keyboard	USB	Depth	12.9" (32.8cm)
Mouse	USB	Master Carton Qty.	6
Microphone	Standard	Weight	
Audio	2.1	Master Carton Wt.	32.2lb (14.64kg)
Video Resolution		Unit Pack Wt.	5.3lb (2.41kg)
2048 x 1536 (DDC2B), 1920x1200 (with adapters)		Unit Wt. w/accessories	1.7lb (0.77kg)
Cable Length		Unit Wt.	1.6lb (.72kg)
6ft (1.8m)			
Cable Connections			
Input	USB		
Output	USB or PS/2		
LEDs			
USB Peripherals	Green		
Port ID	Orange		