

GCS1902


## 2-Port DisplayPort KVMP Switch with USB 3.0 Hub (TAA Compliant)



- Switch between two computers with the push of a button
- Stunning 4K video resolution
- Multiple switching options - via pushbutton, hotkey, or mouse
- 2 x USB 3.0 built-in ports for peripheral sharing
- Cost effective: Cables included, firmware upgradable
- Plug-N-Play

- Control 2 computers using a single keyboard, mouse, and DisplayPort video console
  - Superior video quality – 4K UHD (3840x2160 @ 30Hz)
  - DisplayPort 1.1 compliant & HDCP compliant
  - 2-Port USB 3.0 Hub with SuperSpeed 5Gbps transfer rate
  - DP++ supports HDMI and DVI output<sup>1</sup>
  - Computer selection via front panel pushbuttons, hotkeys, and mouse<sup>2</sup>
  - Independent switching of the KVM, USB, and 2.1 channel audio
  - Supports 7.1 HD audio through DisplayPort<sup>3</sup>
  - Mouse emulation or bypass feature supports most mouse drivers and multifunction mice
  - Multi-platform support – Windows®7, Windows®8.1, Windows®10, Mac®, and Linux®
  - Multilingual keyboard mapping supports English, Japanese, French, and German keyboards
  - Mac® keyboard support and emulation<sup>4</sup>
  - Auto Scan Mode to monitor all computers
  - Power On Detection
  - Hot pluggable
  - Firmware Upgradable
  - All cables included
- <sup>1</sup> Dual-Mode DisplayPort (DP++) requires active HDMI and DVI adapters for most display setups.
- <sup>2</sup> Mouse port switching supported alongside mouse emulation mode using a USB 3-button mouse wheel
- <sup>3</sup> HD audio through DisplayPort cannot be switched independently
- <sup>4</sup> PC keyboard combinations emulate Mac® keyboards. Keyboards only work using their own Operating System





#### Requirements

#### Package Contents

- **Console:**
- DisplayPort compatible monitor
- Standard 104 key wired USB keyboard
- Standard 2 or 3 button wired USB mouse
- Speakers (optional)
- 
- **Computers:**
- DisplayPort port
- USB Type-A port
- Audio ports (optional)
- 
- **Cables:**
- Use only specifically designed IOGEAR DisplayPort KVM Cable sets included

\*Use with video adapter may change performance

## Specifications

Function	GCS1902	Dimensions	GCS1902
<b>Computer Connections</b>		<b>Unit Dimensions</b>	
Direct	2	Height	2.94" (7.47cm)
<b>Port Selection</b>		Length	7.875" (20cm)
Pushbutton, Hotkeys, Mouse (mouse port switching only works with 3-key USB mouse wheel in emulation mode)		Depth	1.69" (4.29cm)
<b>Console Connectors</b>		<b>Unit Package Dimensions</b>	
Monitor	1 x DisplayPort	Height	6.81" (17.3cm)
Keyboard	1 x USB 3.0 Type A	Width	11.25" (28.58cm)
Mouse	1 x USB 3.0 Type A	Depth	4" (10.16cm)
Audio	2 x 3.5mm Mini Stereo Jack (Front and Rear)	<b>Master Carton</b>	
<b>CPU Connectors</b>		Height	14.75" (37.47cm)
Monitor	2 x DisplayPort	Width	12.5" (31.75cm)
Audio	2 x 3.5mm Mini Stereo Jack	Depth	12" (30.48cm)
Keyboard & Mouse	2 x USB 3.0 Type B	Master Carton Qty.	6
<b>Switches</b>		<b>Weight</b>	
F/W Upgrade	1 x USB Type B	Master Carton Wt.	24.7lb (11.24kg)
Port Selection	2 x Pushbutton	Unit Pack Wt.	3.68lb (1.67kg)
<b>Power Connections</b>		Unit Wt.	1.45lb (0.66kg)
1 x DC 5V Jack			
<b>Connectors</b>			
USB			
2 x USB 3.0 Type A (Front and Rear)			
<b>LEDs</b>			
Mode	2 x Orange		
On Line	2 x Green		
KVM	2 x Orange		
Audio	2 x Orange		
USB Peripherals	2 x Green		
<b>Emulation</b>			
Keyboard	USB		
Mouse	USB		
<b>Video Resolution</b>			
2560 x 1600 @ 60Hz, 3840 x 2160 @ 30Hz (4K UHD)			
<b>Scan Interval</b>			
1-99 seconds (5 seconds default)			
<b>Power</b>			
Voltage	DC 5V		
Amps			
<b>Environment</b>			
Operation Temperature	0-50C		
Storage Temperature	-20-60C		
Humidity	0-80% RH, Non-condensing		
<b>Housing</b>			
Case	Metal		
<b>Cable Length</b>			
DisplayPort cables (5ft); USB 3.0 cables (5ft)			

at Home at Work on-the-Go

