

GCS1932-KM

2-Port 4K DisplayPort 1.2 KVMP with Wireless Keyboard and Mouse



- DisplayPort 1.2 computer switch bundle
- Included wireless keyboard and mouse at a fantastic price
- 4K DCI Resolution Support
- Connect up to 3 monitors
- Comfortable typing experience

DisplayPort 1.2 KVMP Switch with Wireless Keyboard and Mouse

IOGEAR's 2-Port DisplayPort 1.2 KVMP bundle comes complete with a set of IOGEAR's state-of-the-art wireless keyboard and mouse. Streamline your 4K setup with this computer switch, IOGEAR's low-profile keyboard and touch sensor mouse. With a combination of Cinema 4K resolution support, the next generation USB3.1 hub, and enhanced user-friendly operation, IOGEAR's DisplayPort 1.2 KVMP Bundle provides the latest innovations in DisplayPort KVM technology and convenience in desktop setup. Your most affordable computer switching connectivity solution is ready for setup straight out-of-the-box!

- **DisplayPort KVMP:**
- Switch between 2 computers at the push of a button
- Control 2 computers using a single keyboard, mouse, and up to 3 DisplayPort monitors
- Superior video quality – Cinema 4K (4096x2160@60Hz)
- DisplayPort 1.2 compliant, HDCP compliant
- 2-Port USB3.1 Gen1 Hub with SuperSpeed 5Gbps transfer rate
- MST (Multi-Stream Transport)¹
- DP++ supports HDMI and DVI output²
- Switch between computers via front panel pushbuttons, hotkeys
- Independent switching of the video, USB, and audio
- Supports superior HD quality audio
- Multi-platform support – Windows®7, Windows®8.1, Windows®10, Mac®, and Linux®
- Auto Scan Mode to monitor all computers
- Power On Detection and hot pluggable
- Firmware Upgradable


- Supports keyboard and mouse emulation
-
- **Wireless Keyboard and Mouse:**
- 2.4 GHz wireless- up to 33ft range
- 1000dpi resolution wireless mouse with touch pad
- Low-profile keys for quiet, comfortable typing
- Touch Mouse supports smooth horizontal and vertical animation scrolling*
- 12 multimedia hotkeys for quick access to your music, e-mail, browser and more
- Chiclet style keyboard layout
- Durable keys with a durability of 10 million cycles

¹ MST requires two monitors capable of DisplayPort 1.2 daisy chaining, or use of a powered DisplayPort MST Hub. PC Source must be DisplayPort 1.2 compliant. A DisplayPort 1.1a monitor can be the last monitor in a DP1.2 chain

² Dual-Mode DisplayPort (DP++) does not require an active adapter for most single display setups. Active DisplayPort adapters are recommended if you are unsure of the video source's DP++ compatibility

³ HD audio through DisplayPort cannot be switched independently





Requirements

- **Console**
- DisplayPort compatible monitor
- **Computer**
- DisplayPort port
- USB Type A port
- **Wireless Keyboard and Mouse**
- Windows® 7, Windows® 8, Windows® 8.1, Windows® 10
- Mac OS X 10.3+*

Package Contents

- 1 x 2-Port DisplayPort 1.2 KVMP
- 1 x Wireless Keyboard
- 1 x Wireless Touch Sensor Mouse
- 1 x USB RF Receiver
- 2 x DisplayPort Cables (5ft.)
- 2 x USB 3.0 Cables (6ft.)
- 4 x Audio Cables (6ft.)
- 1 x Power Adapter
- 1 x Manual

*Some function keys may not work with older Mac OS Systems

**Use with video adapter may change performance

Specifications

Function	GCS1932-KM	Dimensions	GCS1932-KM
Computer Connections		Master Carton	
Direct	2	Height	10" (25.4cm)
Port Selection		Width	9" (22.86cm)
Console Connectors		Depth	22" (55.88cm)
Monitor	1 x DisplayPort	Master Carton Qty.	1
Keyboard	1 x USB Type A	Weight	
Mouse	1 x USB Type A	Master Carton Wt.	5.98lb (2.72kg)
Audio	x 3.5mm Mini Stereo Jack (Front and Rear)		
Microphone	x 3.5mm Mini Stereo Jack (Front and Rear)		
CPU Connectors			
Monitor	2 x DisplayPort		
Keyboard & Mouse	2 x USB 3.1 Gen1 Type B		
Audio	2 x 3.5mm Mini Stereo Jack		
Microphone	2 x 3.5mm Mini Stereo Jack		
Switches			
F/W Upgrade	1 x USB Type B		
Port Selection	2 x Pushbuttons		
Connectors			
USB	2 x USB 3.1 Gen1 Type A		
LEDs			
Mode	2 x Orange		
KVM	2 x Orange		
Audio	2 x Orange		

Emulation

Keyboard USB

Mouse USB

Video Resolution 4096 x 2160 @ 60Hz (4K DCI)**Scan Interval** 1-99 seconds (5 seconds default)**Power**

Voltage DC 5.3V

Environment

Operation Temperature 0-50C

Storage Temperature -20-60C

Humidity 0-80% RH, Non-condensing

Housing

Case KVM: Metal; Keyboard & Mouse: Plastic

Operating System Support Keyboard: Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Mac OS X 10.3+**Interface** Keyboard & Mouse: USB 2.0 and USB 1.1**Resolution** Mouse: 1000dpi**Radio Frequency** Keyboard & Mouse: 2.4GHz**Battery Type** Keyboard: 1 x AAA, Mouse: 1 x AA**Operating Range** Keyboard & Mouse: Up to 33ft (10m)