IOGEAR®

GCS614A

MiniView™ Micro PS/2 Audio KVM Switch with cables

Introducing the four port MiniView™ Micro Audio KVM switch from IOGEAR - a simple solution for those with more PCs than hands. Use one keyboard, one monitor and one mouse to control four PCs or Macintosh systems*, and share the multimedia speakers among them. This self-powered KVM switch features mouse & keyboard emulation to ensure smooth operation, as well as support for Plug-n-Play monitors and most wheel mice. Patented VSE Video Signal Enhancement® technology provides rich, 32-bit color at resolutions up to 2048 x 1536. With KVM cables (6' long) molded into the unit, all you need to do is to plug it into your computers, and you've got a complete KVM solution from IOGEAR. * Macintosh support requires IOGEAR's Mac Adapter.

- The smallest 4-port KVM switch available with audio support
- Use one keyboard, monitor and mouse to control four computers
- Share multimedia speakers among four computers
- 6' long molded-in cables to simplify setup
- Microsoft Intellimouse, Logitech FirstMouse+, MouseMan+, and most PS/2 mice are supported

- Port selection through convenient Hot Keys
- PS/2 mouse emulation for error-free boot-up
- Save space and reduce desktop clutter
- Plug-n-Play monitor support
- Support video resolutions up to 2048 x 1536
- LEDs allow for easy status monitoring
- 3 Year Limited Warranty

IOGEAR®

Requirements

- A VGA or Multisync monitor
- 2.0 Powered desktop speakers (optional)

- Operating System
    - Windows XP, Windows Vista (32-bit / 64-bit), Windows 8.x

Package Contents

- 1 4-port Miniview Audio Micro KVM
- 1 User manual
- 1 Quick start guide
- 1 Warranty registration card

Specifications

Function	GCS614A
Housing	
Case	Plastic
CPU Connectors	
Mouse	4x 6 pin mini-DIN male (green)
Keyboard	4x 6 pin mini-DIN male (purple)
Monitor	4 x 6 HDB-15 male (blue)
Audio	4 x Earphone Plug (speaker)
Console Connectors	
Mouse	1 x 6 pin mini-DIN female (green)
Keyboard	1 x 6 pin mini-DIN female (purple)
Monitor	1 x HDB-15 female (blue)
Audio	1x Earphone Jack (speaker)
LEDs	
Selected	4
Port Selection	Hot Keys
Video Resolution	2048 x 1536; DDC2B
Scan Interval	5 Seconds
Computer Connections	
Direct	4
Operating Temperature	0-50° C
Storage Temperature	-20 - 60° C
Humidity	0-80% RH Non-condensing

Dimensions	GCS614A
Unit Dimensions	
Height	1.023 in.(2.6 cm.)
Length	3.523 in.(8.95 cm.)
Width	2.83 in.(7.19 cm.)
Inner Pack	
Height	11.25 in. (21.6 cm)
Length	8.5 in. (21.6 cm)
Width	10.5 in. (26.67 cm)
Inner Pack Qty.	3
Unit Package Dimensions	
Height	12.25 in. (31.i cm)
Width	7.5 in. (19 cm)
Depth	3.5 in. (8.89 cm.)
Master Carton	
Height	12.5 in. (31.75 cm)
Width	17.25 in. (43.8 cm)
Depth	11 in. (28 cm)
Master Carton Qty.	6
Weight	
Master Carton Wt.	16 lb. (7.25 kg)
Inner Pack Wt.	7.3 lb. (3.31 kg)
Unit Pack Wt.	2.25 lb. (1 kg)
Unit Wt.	1 lbs. (0.45 kg.)