

GCS712U

## MiniView? Micro USB Audio KVM Switch with cables



Introducing the two port MiniView™ Micro USB Audio KVM switch from IOGEAR – the simplest way to manage two PCs or Macs from a single PS/2 keyboard, monitor and PS/2 mouse and share the multimedia speakers among them. This self-powered KVM switch features mouse and keyboard emulation to ensure smooth operation, as well as support for Plug-n-Play monitors and most wheel mice. Patented VSE Video Signal Enhancement® technology provides rich, 32-bit color at resolutions up to 2048 x 1536. With KVM cables (6' long) molded into the unit, all you need to do is to plug it into your computers, and you've got a complete KVM solution from IOGEAR.

- The smallest 2-port KVM switch available with audio support
- Use one keyboard, monitor and mouse to control two computers
- Share multimedia speakers among two computers
- 6' long molded-in cables to simplify setup
- Support for Microsoft Intellimouse, Logitech FirstMouse+, MouseMan+, and most PS/2 mice
- Port selection through convenient Hot Keys
- PS/2 mouse emulation for error-free boot-up
- Saves space and reduces desktop clutter
- Plug-n-Play monitor support
- Supports video resolutions up to 2048 x 1536
- No software required
- Built in AutoScan mode
- LEDs allow for easy status monitoring
- 3 Year Limited Warranty



## Requirements

- Computers with USB connections, and HDB15 VGA connection
- PS/2 Keyboard and mouse
- To share audio, a multimedia sound card is required. Only support 2-piece, powered speakers systems.

## Package Contents

- 1 2-port MiniView Audio Micro KVM
- 1 User manual
- 1 Quick start guide
- 1 Warranty registration card

## Specifications

Function GCS712U

### Housing

Case Plastic

### CPU Connectors

Monitor 2 x 6 HDB-15 male (blue)

Audio 2 x Earphone Plug (speaker)

Keyboard & Mouse 2 x USB Type A

### Console Connectors

Mouse 1 x 6 pin mini-DIN female (green)

Keyboard 1 x 6 pin mini-DIN female (purple)

Monitor 1 x HDB-15 female (blue)

Audio 1x Earphone Jack (speaker)

### LEDs

Selected 4

Port Selection Hot Keys

Video Resolution 2048 x 1536; DDC2B

Scan Interval 5 Seconds

### Computer Connections

Direct 2

Operating Temperature 0-50° C

Storage Temperature -20 - 60° C

Humidity 0-80% RH Non-condensing

Dimensions GCS712U

### Unit Dimensions

Height 2.5 cm. (0.98 in.)

Length 12.0 cm. (4.72 in.)

Width 4.9 cm. (1.93 in.)

### Inner Pack

Height 10.25 in. (26 cm)

Length 7.125 in. (018 cm )

Width 9 in. ( 22.86 cm)

Inner Pack Qty. 3

### Unit Package Dimensions

Height 7.5 in. (19 cm)

Width 5.5 in. (14 cm)

Depth 2.75 in. ( 7 cm)

### Master Carton

Height 11 in. (28 cm)

Width 18.5 in. ( 47 cm)

Depth 14.5 in. (36.83 cm)

Master Carton Qty. 12

### Weight

Master Carton Wt. 17.8 lb. (8 kg)

Inner Pack Wt. 4.05 lbs. (1.84kg)

Unit Pack Wt. 1.2 lb. (0.54kg)

Unit Wt. 0.9 Lb. (0.41 kg.)