

GCS78KIT

8-Port KVM Switch Kit , PS/2, w/KVM Cables



- Use one keyboard, monitor and mouse to control 8 computers
- Includes four 6 ft KVM cables and four 10ft KVM cables
- Connected computers can be added or removed from the setup without disturbing the other computers

- Plug-n-Play monitor support; high-resolution video support (up to 1920 x 1440)
- Easy to install - no software required
- Easy to operate use push button at the front and hot keys to switch port
- Built in AutoScan mode
- LEDs allow for easy status monitoring



Requirements

- Computers with PS/2 connections, and HDDB15 VGA connection

Package Contents

- 1 x 8-Port MiniView PS/2 KVM switch
- 1 x Power adapter
- 1 x Rack mount kit
- 1 x Quick start guide
- 1 x Warranty/Registration card
- 4 x KVM Cables (6', PS/2) (IOGEAR Part Number G2L5002P)
- 4 x KVM cables (10', PS/2) (IOGEAR Part Number G2L5003P)

Specifications

Function	GCS78KIT	Dimensions	GCS78KIT
Housing		Unit Dimensions	
Case	Metal	Height	1.75 in. (4.45 cm.)
CPU Connectors		Depth	6 in. (15.24 cm.)
Mouse	8x6 pin mini-DIN Female (PS/2)	Width	17 in. (43.18 cm.)
Keyboard	8x6 pin mini-DIN Female (PS/2)	Unit Package Dimensions	
Monitor	8xHDD15 Male	Height	9.5 in. (24 cm)
Console Connectors		Width	5.125 in. (13 cm)
Mouse	1x6 pin mini-DIN Female (PS/2)	Depth	21.125 in. (53.6 cm)
Keyboard	1x6 pin mini-DIN Female (PS/2)	Master Carton	
Monitor	1xHDD15 Female	Height	10" (25.4cm)
Power		Width	22" (55.88cm)
Voltage	DC 9V	Depth	9" (22.86cm)
Amps	400 mA(Max)	Master Carton Qty.	1
LEDs		Weight	
Power On	1	Master Carton Wt.	14.4lb (6.55kg)
Selected	8	Unit Pack Wt.	6.4lb (3kg)
On Line	8	Unit Wt.	7.8lb (3.51kg)
Port Selection	Push Buttons, Hot Keys		
Power Consumption	1.08W max		
Video Resolution	1920x1440; DDC2B		
Scan Interval	5 seconds		
Emulation			
Keyboard	PS/2		
Mouse	PS/2		
Computer Connections			
Direct	8		