

GCS84B

MiniView™ SE KVM Switch Kit w/Cables



A Faster Way To Connect! Once again, IOGEAR raises the bar on quality KVMs. These desktop PS/2 KVMs feature the latest in micro-design and technology. Setup is fast and easy; simply plug cables into their appropriate ports. The four PS/2 console ports are on the front of the unit for easy and convenient access. IOGEAR's MiniView™ SE GCS84B provides two convenient methods to access the connected computers: use push-button selection switches, located on the unit's front panel; or type Hot Key combinations from the keyboard. There is no better way to save time and money than with IOGEAR's MiniView™ SE GCS84B. Cables included!

- Use one keyboard, monitor and mouse to control up to four computers
- Works with PS/2 compliant computers
- Operating system independent
- Supports Mac and SUN *
- Plug-n-Play monitor support
- Supports video resolutions up to 2048 x 1536
- Easy to install - no software required
- Easy to operate - push buttons or Hot Keys
- Keyboard and mouse emulation for error free computer booting
- Built in AutoScan mode to monitor all computers
- LEDs allow for easy status monitoring
- Increases desk space and productivity
- Decreases power and equipment costs
- Trim-line, compact design
- 3 Year Limited Warranty

* Additional adapters required to support Mac DB and SUN



Requirements

- PS/2 Enabled/Compliant computer system

Package Contents

- 1 MiniView SE 4-Port KVM switch
- 4 sets of premium bonded KVM cables
- 1 installation manual
- 1 quick start guide
- 1 product registration card

Specifications

Function	GCS84B
Housing	
Case	Metal
CPU Connectors	
Mouse	4 x 6 pin mini-DIN Female (PS/2)
Keyboard	4 x 6 pin mini-DIN Female (PS/2)
Monitor	4 HDB-15 Male (Std. VGA/SVGA)
Console Connectors	
Mouse	1 x 6 pin mini-DIN Female (PS/2)
Keyboard	1 x 6 pin mini-DIN Female (PS/2)
Monitor	1 HDB-15 Female (Std. VGA/SVGA)-
Power	
Voltage	DC 9V
Amps	40mA (Max.)
LEDs	
Selected	4
On Line	4
Port Selection	
	Pushbutton Switch / Hot Keys
Power Consumption	
	DC 9V 360 mW (Max.)
Video Resolution	
	2048 x 1536 (Max.); DDC/ DDC2B/ DDC2AB
Scan Interval	
	5 sec.
Emulation	
Keyboard	PS/2; AT
Mouse	PS/2
Computer Connections	
Direct	4
Daisy Chain or Cascading	64 (External power supply may needed)
Power Adaptor Part #	
for North America	0AD1-0909-031

Dimensions	
Unit Dimensions	
Height	1.7 in. (4.32 cm.)
Length	3 in. (7.62 cm.)
Width	8 in. (20.32 cm.)
Unit Package Dimensions	
Height	4 in. (10.16 cm.)
Width	13 in. (33.02 cm.)
Depth	8.5 in. (21.59 cm.)
Master Carton	
Height	14 in. (35.56 cm.)
Width	13 in. (33.02 cm.)
Depth	17.5 in. (44.45 cm.)
Master Carton Qty.	6
Weight	
Master Carton Wt.	27.75 lbs. (12.49 kg.)
Unit Pack Wt.	4.2 Lbs. (1.89 kg.)
Unit Wt.	1.65 Lbs. (0.74 kg.)