

GCS92

## MiniView? Micro DVI PS/2 KVM Switch with cables and audio



The two port Mini View™ Micro DVI PS2 KVM switch from IOGEAR represents a simple method for sharing one DVI monitor, Mouse, Keyboard, Speaker set and Microphone between two computers.

The GCS92 employs two switching methods. The first is a simple remote port selector switch that allows one tap switching. Due to its small size, the remote port can be placed in a convenient location on your desk. The second method is by hotkey so there is no need to remove your fingers from the keyboard

Hot key switching allows you to independently switch KVM and Audio functionality, use your Internet phone from one computer while working on the other.

- Use one DVI monitor, keyboard, and mouse to control two DVI computers.
- One tap switching with the included remote port selector switch.
- Hot key switching allows the focus of the KVM and the audio functions to be independently switched between your computers
- Listen to music from one computer while working on the other
- Reprogramable Hot key activation for keyboards without a Scroll Lock key
- Plug-n-Play support for video resolutions up to 1920 X 1200 @ 60 Hz
- PS/2 mouse and keyboard emulation for error-free boot-up and instantaneous recognition when switching computers
- Supports two button scroll wheel mice and standard keyboards
- Asymmetrical CPU cables
- LEDs allow for easy status monitoring
- Molded-in cables to simplify setup, nothing else to buy
- 3 Year Limited Warranty



## Requirements

- A DVI monitor capable of the highest resolution that you will be using on any computer in the installation
- A PS/2 style keyboard and mouse
- Speakers and microphone (optional)
- 
- Computers:
- The following equipment must be installed on each computer that is to be connected to the system:
- A DVI-D video port
- 6-pin mini-DIN (PS/2 style) keyboard port, and a 6-pin mini-DIN (PS/2 style) mouse port
- Speaker and microphone ports (optional)

## Package Contents

- 1 x 2 port DVI PS2 KVM with built in cables
- 1 x Remote port selector switch
- 1 x Quick start guide

## Specifications

Function	GCS92	Dimensions	GCS92
<b>Housing</b>		<b>Inner Pack</b>	
Case	Plastic	Height	7.9in (20cm)
<b>CPU Connectors</b>		Length	11.14in (28.3cm)
Mouse	2x6 pin mini-DIN Female (PS/2)	Width	9.25in (23.5cm)
Keyboard	2 X 6-pin Mini-DIN Male (Purple)	Inner Pack Qty.	3 ea
Monitor	2xDVI-D (DVI Digital only)	<b>Unit Package Dimensions</b>	
Microphone	2 x Mini Stereo Plug Male (Pink)	Height	2.75in (7cm)
Audio	2 x Mini Stereo Plug Male (Green)	Length	10.375 (26.3cm)
Keyboard & Mouse	2 x DVI - D Male (Black)	Width	7.75 (19.7cm)
<b>Console Connectors</b>		<b>Master Carton</b>	
Mouse	6-pin Mini-DIN Female (Green)	Height	12in (30.7cm)
Keyboard	6-pin Mini-DIN Female (Purple)	Width	9.7in (24.6cm)
Monitor	DVI-D Male (Black)	Depth	16.5in (42cm)
Microphone	Mini Stereo Jack Female (Pink)	Master Carton Qty.	6 ea
Audio	Mini Stereo Jack Female (Green)	<b>Weight</b>	
<b>LEDs</b>		Master Carton Wt.	14.3lbs (6.5kg)
Selected	2	Inner Pack Wt.	6.5lbs (2.96kg)
Manual select	Active port	Unit Pack Wt.	2.0 (1.0 kg)
<b>Port Selection</b>	Hot Keys / Manual Switch	Unit Wt. w/accessories	1.66lbs ( 0.753kg)
<b>Video Resolution</b>	1920 x 1200 @ 60Hz	Unit Wt.	1.3lbs(0.589 kg)
<b>Scan Interval</b>	3, 5, 10, 20 seconds		
<b>Emulation</b>			
Keyboard	PS/2		
Mouse	PS/2		
<b>Computer Connections</b>			
Direct	2		
<b>Cable Length</b>	Console (3 ft. 9 in. / 1.2 m.)		
<b>Cable Distance</b>	Computer Side A (3 ft. 9 in. / 1.2 m.) - Computer Side B (1 ft. 11 in. / .6 m.)		