

GCS922MDPKIT

2-Port USB DVI and Mini DisplayPort Cable KVM Kit

- Switch between two computers with the push of a button
- Offers the flexibility to mix and match computer connections: DVI and DisplayPort
- Includes 2 x DisplayPort to DVI adapters
- No external power needed
- Save Cabling Costs: ALL cables are included




2-Port Cable DVI / Mini DisplayPort KVM Switch


- Switch between two computers with the push of a button
 - Offers the flexibility to mix and match computer connections: DVI and Mini DisplayPort
 - Includes 2 x Mini DisplayPort to DVI adapters
 - No external power needed
 - Cost effective, Plug-N-Play solution
-
- Connect and control two DVI-D or Mini DisplayPort USB 2.0 interface computers with a single keyboard and mouse
 - USB mouse port can be used for USB peripheral sharing, such as external storage drive
 - Computer Selection via push-button Remote Port Selector
 - Video resolution – up to 1920 x 1200 @60Hz
 - Supports USB hot-plugging
 - Power supply not required
 - All cables are included
-
- Mini DisplayPort to DVI Adapters:
 - Converts your Mini DisplayPort to DVI so you can connect to your DVI projector, TV or monitor.
 - Works with Apple® iMac® or MacBook®
 - Compliant with Mini DisplayPort Specification 1.1a for both 1.62 Gbps and 2.7 Gbps
 - Support full Mini DisplayPort link tracking
 - Supported resolutions:
 - Full HD 1080p
 - 1920x1200
 - Compliant with DVI 1.0 up to 1.65Gbps
 - Support interrupt request output for expansion function
 - Support Deep Sleep Mode (suspend mode)



Solution 1



Solution 2



Requirements

- Console:
- 1 DVI display
- 1 set of USB keyboard and mouse
-
- Computers:
- 1 DVI-D Port or Mini DisplayPort
- 1 USB Ports
-
- Operating Systems:
- Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10
- Mac OS 9 to 10.x
- Oracle® Solaris
- Linux®, Unix and other USB supported systems*

Package Contents

- 1 x GCS922U
- 2 x Mini DisplayPort to DVI Adapters
- 1 x Quick Start Guide
- 1 x Warranty

*Additional drivers and support may be needed

Specifications

Function	GCS922MDPKIT	Dimensions	GCS922MDPKIT
Computer Connections		POP Information	
Direct	2	10" Peg Hook	5
Console Connectors		6" Peg Hook	3
Monitor	1 x DVI-D Female	Unit Dimensions	
Keyboard	1 x USB Type A Female	Height	1.06" (2.69cm)
Mouse	1 x USB Type A Female	Depth	4.06" (10.3cm)
CPU Connectors		Length	3.44" (8.74cm)
Monitor	2 x DVI-D Male; 2 x Mini DisplayPort Male (adapters)	Unit Package Dimensions	
Keyboard & Mouse	2 x USB Type A Male	Width	6.13" (15.6cm)
LEDs		Height	8.81" (22.4cm)
On Line	2 x Green	Depth	2.25" (5.72cm)
Video Resolution	1900x1200 @60Hz	Master Carton	
Environment		Width	6.75" (17.1cm)
Storage Temperature	-20~60°C	Height	15" (38.1cm)
Operation Temperature	0~50°C	Depth	8" (20.3cm)
Humidity	0~80%; Non-condensing	Master Carton Qty.	6
Port Selection	Remote Switch	Weight	
Cable Length	2 x 4ft. ea KVM cables; 1 x 6ft. Remote Switch	Master Carton Wt.	7.2lb (3.27kg)
Cable Type	Bonded USB KVM	Unit Pack Wt.	1.1lb (0.5kg)
Housing		Unit Wt. w/accessories	0.85lb (0.39kg)
Case	Plastic	Unit Wt.	0.75lb (0.34kg)