

GCS932UB

## 2-Port USB DVI-D Cable KVM with Audio and Mic.

Plug-N-Play - Share two computers using a keyboard, mouse and DVI monitor (1920x1200). Cables included.



The GCS932UB 2-Port USB DVI Cable KVM Switch with Audio from IOGEAR represents a simple method for sharing one DVI monitor, mouse, keyboard, speaker set and microphone between two computers. The product supports 32 bit color at resolutions up to 1920 X 1200 @ 60 Hz and its mouse and keyboard emulation ensures uninterrupted operation when switching computers.

It utilizes 2 convenient switching methods, first being a small simple push-button remote switch that fits any desired location on your desk and the other is by hotkey, which allows you to independently switch control and audio functions between computers.

Equipped with the IOGEAR's DynaSync\* which remembers your monitor's ideal resolution and refresh rate, making it possible to boot all your computers simultaneously, and switch back and forth between computers, while still maintaining the ideal resolution of the monitor.

- Control 2 computer with one keyboard, mouse and monitor
- 2-Port DVI KVM, cables included
- Video resolution: 1920x1200 @ 60Hz
- Port switching via remote switch button, mouse or hotkeys
- Hotkeys allows independent KVM and audio switching between computers
- 2.1 stereo sound and microphone support
- USB 2.0 Peripheral Sharing via mouse port. Connect a powered USB Hub to expand your USB connectivity\*
- IOGEAR's DynaSync\*\* reads and remembers the monitor's parameters (EDID) so there is no delay or change of video resolution when switching between, or booting computers
- USB mouse and keyboard emulation for error-free boot-up and instantaneous recognition when switching computers
- Power-On Detection – If one of the computers is powered off, it will automatically switch to the next powered-on computer
- Re-programmable Hotkey activation for keyboards without a Scroll Lock key
- Mouse emulation can be disabled to support mice with special keys
- Mac and Sun keyboard support
- Firmware upgradeable
- Plug-N-Play

\*Mouse emulation must be disabled for this feature to function correctly.

\*\*IOGEAR's DynaSync provides the EDID support for Windows 7



### How does it work?

#### Standard Setup

- Connect your monitor, keyboard, mouse, powered speakers, and mic to the KVM
- Connect the set of USB KVM cables to each computer
- Press the remote switch button to switch between computers



#### Advanced Setup

- Connect your monitor, keyboard, powered speakers, and mic to the KVM
- Connect your powered USB 2.0 Hub to the mouse port on the KVM; connect your mouse, printer, and/or storage device to the powered USB Hub\*
- Connect the set of USB KVM cables to each computer
- Press the remote switch button to switch between computers



### Requirements

- 
- **Console:**
- DVI monitor
- Standard 104 key wired USB keyboard
- Standard 2 or 3 button wired USB mouse
- Speakers and microphone
- 
- **Computers:**
- DVI port
- Type "A" USB port
- Audio ports
- 
- **Operating Systems:**
- Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10
- Mac OS 9 to 10.x
- Oracle® Solaris
- Linux®, Unix and other USB supported systems\*

### Package Contents

- 1 x 2-Port USB Cable KVM
- 1 x Remote Switch Button
- 1 x Installation Guide
- 1 x Warranty Card

\*Additional drivers and support may be needed

\*\*IOGEAR's DynaSync provides the EDID support for Windows(R) 7

## Specifications

Function	GCS932UB
<b>Computer Connections</b>	
Direct	2
<b>Console Connection</b>	1
<b>Port Selection</b>	Hotkey, Mouse or Remote Switch Button
<b>Console Connectors</b>	
Keyboard	1 x USB Type A Female
Mouse	1 x USB Type A Female
Monitor	1 x Single Link DVI-D Female
Audio	1 x Mini Stereo Jack Female (Green)
Microphone	1 x Mini Stereo Jack Female (Pink)
<b>CPU Connectors</b>	
Keyboard & Mouse	4 x USB Type A Male (Purple for Keyboard and Black for Mouse)
Monitor	2 x Single Link DVI-D Male
Audio	2 x Mini Stereo Jack Male (Green)
Microphone	2 x Mini Stereo Jack Male (Pink)
<b>LEDs</b>	
Port ID	2 x Green
<b>Cable Length</b>	1.2m
<b>Emulation</b>	
Keyboard	USB
Mouse	USB
<b>Switches</b>	
F/W Upgrade	USB
<b>Video Resolution</b>	1920 x 1200 @ 60Hz; DDC2B
<b>Scan Interval</b>	Default 5 Seconds (3, 5, 10 or 20 sec.)
<b>Environment</b>	
Operation Temperature	0~50C
Storage Temperature	-20~60C
Humidity	0~80% RH; Non-condensing
<b>Housing</b>	
Case	Plastic

Dimensions	GCS932UB
<b>POP Information</b>	
10" Peg Hook	3
6" Peg Hook	2
<b>Unit Dimensions</b>	
Width	4.38in
Height	1.00in
Depth	2.94in
<b>Unit Package Dimensions</b>	
Width	6.5in
Height	9.25in
Depth	2.75in
<b>Master Carton</b>	
Width	9.50in
Height	7.50in
Depth	16.25in
Master Carton Qty.	6
<b>Weight</b>	
Master Carton Wt.	8.78lb
Unit Pack Wt.	1.32lb
Unit Wt.	1.06lb