

GCS982U

2-Port Dual-Link DVI Cable KVM with Audio

Plug-N-Play - Share two computers using a keyboard, mouse and DVI monitor (2560x1600@60Hz). Cables included.



2-Port Dual-Link DVI Cable KVM with Audio

IOGEAR's 2-Port USB Dual-Link DVI Cable KVM Switch with Audio offers a simple method for switching between two computers from one dual-link DVI monitor, mouse, keyboard, and a set of speaker - microphone. This compact cable KVM comes ready with built-in KVM cables, eliminating that extra step connecting your computers, console, and the KVM itself. Customize your settings using the programmed hotkey combination with features such as Auto Scan, Port Switching, Mouse and Keyboard Emulation, Power on Detection, and so on. A complete KVM solution in a compact form factor.

Robust Features & Plug-N-Play

The 2-Port USB Dual-Link DVI Cable supports mouse and keyboard emulation, ensuring uninterrupted operation when switching computers. Simply switch between the two connected computers by hotkey, remote pushbutton, or 3-button mouse. Also, mouse and keyboard emulation. Enjoy your viewing up to Dual-Link DVI resolutions of 2560x1600 and audio of 2.1.

- Control 2 computers with one keyboard, mouse and monitor
- 2-Port DVI cable KVM switch
- Dual-link DVI resolution up to 2560x1600 @ 60Hz
- Port switching via remote switch button, mouse or hotkeys
- Hotkeys allows independent KVM and audio switching between computers
- 2.1 stereo sound and microphone support
- USB 2.0 Peripheral Sharing via mouse port - Connect a powered USB hub to expand your USB connectivity*
- IOGEAR's DynaSync** technology reads and remembers the monitor's parameters (EDID) so there is no delay or change of video resolution when switching between, or booting computers
- USB mouse and keyboard emulation for error-free boot-up and instantaneous recognition when switching computers
- Power-On Detection - If one of the computers is powered off, it will automatically switch to the next powered-on computer
- Re-programmable Hotkey activation for keyboards without a Scroll Lock key
- Mouse emulation can be disabled to support mice with special keys
- Mac and Sun keyboard support
- Firmware upgradeable
- Plug-n-Play; No software required


*Mouse emulation must be disabled for this feature to function correctly

**IOGEAR's DynaSync provides the EDID support for Windows 7



How does it work?

- Connect your computers to the KVM switch with the included KVM cables
- Connect your mouse, keyboard, and monitor to the console side of the KVM
- If you are using 2.1 audio and mic, connect the included audio and mic cables
- Press the remote switch button to switch between two DVI computers



Requirements

Console:
 DVI monitor
 Standard 104 key wired USB keyboard
 Standard 2 or 3 button wired USB mouse
 Speakers and microphone

Computers:
 DVI port
 Type "A" USB port
 Audio ports

Operating Systems:
 Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10
 Mac OS 9 to 10.x
 Oracle® Solaris
 Linux®, Unix and other USB supported systems*

*Additional drivers and support may be needed

**IOGEAR's DynaSync provides the EDID support for Windows(R) 7

Package Contents

- 1 x 2-Port USB DUAL-LINK DVI Cable KVM
- 1 x Remote Switch Button
- 1 x Quick Installation Guide
- 1 x Warranty Card

Specifications

Function	GCS982U
Computer Connections	
Direct	2
Console Connection	1
Port Selection	Hotkey, Mouse or Remote Switch Button
Console Connectors	
Keyboard	1 x USB Type A Female
Mouse	1 x USB Type A Female
Monitor	1 x Dual-Link DVI-D Female
Audio	1 x Mini Stereo Jack Female (Green)
Microphone	1 x Mini Stereo Jack Female (Pink)
CPU Connectors	
Keyboard & Mouse	4 x USB Type A Male (Purple for Keyboard and Black for Mouse)
Monitor	2 x Dual-Link DVI-D Male
Audio	2 x Mini Stereo Jack Male (Green)
Microphone	2 x Mini Stereo Jack Male (Pink)
LEDs	
Port ID	2 x Green
Cable Length	1.2m
Emulation	
Keyboard	USB
Mouse	USB
Switches	
F/W Upgrade	USB
Video Resolution	2560 x 1600 @ 60Hz; DDC2B
Scan Interval	Default 5 Seconds (3, 5, 10 or 20 sec.)
Environment	
Operation Temperature	0-50C
Storage Temperature	-20-60C
Humidity	0-80% RH; Non-condensing
Housing	
Case	Plastic

Dimensions	GCS982U
POP Information	
10" Peg Hook	3
6" Peg Hook	2
Unit Dimensions	
Width	4.75" (12.1cm)
Height	3.75" (9.5cm)
Depth	1" (2.5cm)
Unit Package Dimensions	
Width	6.5" (15.9cm)
Height	9.25" (23.5cm)
Depth	2.75" (7.0cm)
Master Carton	
Width	9.5" (24.1cm)
Height	7.5" (19.1cm)
Depth	16.25" (41.3cm)
Master Carton Qty.	6
Weight	
Master Carton Wt.	9.85lb (4.47kg)
Unit Pack Wt.	1.50lb (0.68kg)
Unit Wt.	1.20lb (0.54kg)