

GDPSP2

2-Port DisplayPort 1.2 Cinema 4K Splitter & Multi- Monitor MST Hub (TAA)



- Connect 2 independent displays from a single DisplayPort 1.2 video output
- Mirror or extend a desktop across 2 displays from a computer with 1 DisplayPort output
- Enjoy Cinema 4K video resolutions up to 4096 x 2160 @ 60HZ

2-Port DisplayPort Cinema 4K Splitter and MST Hub

Connect two displays from a single DisplayPort 1.2-enabled computer with the IOGEAR 2-Port DisplayPort Splitter/MST Hub. Increase productivity and workflow by expanding the amount of usable screen space on two independent screens for multi-document viewing, media streaming, and content/web browsing, or mirror your computer's display across two monitors to allow remote viewing applications such as monitoring equipment diagnostics or the status of a remote server.


Cinema 4K Video Support

IOGEAR's 2-Port DisplayPort 1.2 Splitter and MST Hub supports Cinema 4K resolutions up to 4096 x 2160 @ 60Hz and is ideal for use with applications such as medical imaging, graphic design, gaming, and more.

- Connect 2 independent displays from a single DisplayPort 1.2 video output
- Mirror or extend a desktop across 2 displays from a computer with 1 DisplayPort output
- Enjoy Cinema 4K video resolutions up to 4096 x 2160 @ 60HZ
- With DisplayPort 1.2 Graphic Cards:
 - 2 Monitors: Up to 4K 4096 x 2160 (DisplayPort/HDMI)
- Supports 7.1 digital audio surround sound
- Push-button toggle between Single Stream Transport (SST) and Multi-Stream Transport (MST)
- DPCP and HDCP compliant
- No driver or software installation needed
- Supports DisplayPort 1.2a; HDCP 1.3



Extend Mode MST



OR

Split Mode SST



Requirements

- **Hardware:**
- Computer with DisplayPort 1.2 compatible graphics card
- 2 Monitors with DisplayPort ports
-
- **Optional:**
- G2LDPDP02 DisplayPort to DisplayPort Cable

Package Contents

- 1 x GDPSP2 2-Port DisplayPort Splitter / MST Hub
- 1 x Power Adapter
- 1 x Quick Start Guide
- 1 x Warranty Card

Specifications

Function	GDPSP2	Dimensions	GDPSP2
Cable Connections		Unit Dimensions	
Input	DisplayPort 1.2	Height	1" (2.5 cm)
Output	DisplayPort	Length	3" (7.6 cm)
Connectors		Depth	4.4" (11.1 cm)
Video Input	1 x DisplayPort Female	Unit Package Dimensions	
Video Output	2 x DisplayPort Female	Height	2.32" (5.9 cm)
Data Rate		Width	9.4" (23.8 cm)
Environment		Depth	6.3" (16 cm)
Humidity	20~90% RH (Non Condensing)	Master Carton	
Operation Temperature	32°F~104°F (0°C~40°C)	Height	10.04" (25.5 cm)
Storage Temperature	-4°F~140°F (-20°C~60°C)	Width	14.89" (37.8 cm)
Housing		Depth	7.17" (18.2 cm)
Case	Metal	Master Carton Qty.	6
LEDs		Weight	
Input	1	Master Carton Wt.	8.95 lb
Output	2	Unit Pack Wt.	1.3 lb (0.6 kg)
Power		Unit Wt.	0.45 lb (0.2 kg)
Amps	2A		
Voltage	DC 5V		
Video Resolution			
Audio			
Codec	2-Ch LPCM / AC3 / DTS		
Sample Rate	32-192kHz		