

GFH610

FireWire Hub



- IEEE 1394 & 1394OHCI v1.0 and IEEE 1394A v2.0 compliant
- 100, 200, 400 Mbps data transfer rate
- Supports hot swapping
- PC 98 and PCI power management v2.2 compliant

- Works with DV camcorders, harddrives, digital cameras, removable drives, scanners, Sony's Playstation II, etc.
- DC input terminal for optional external power supply
- Six IEEE 1394 ports
- Six-pin IEEE 1394 I/O connectors
- Small size for convenient placement
- Three Year Warranty



Requirements

For PC Users

- Windows® 98, 98SE, 2000, ME, XP

For MAC Users

- Mac OS 8.6 or Greater

Package Contents

- GFH610 - 6 Port FireWire Hub
- Warranty card
- Manual
- DC 9V 600mA Power Adapter
- Six-foot 6-6 Pin FireWire Cable

Specifications

Function	GFH610	Dimensions	GFH610
Housing		Unit Package Dimensions	
Case	Plastic, Plastic	Height	6.375 in.
LEDs		Width	2.375 in.
Power On	1, 1	Depth	9.125 in.
Power Consumption		Master Carton	
DC 9.0V (adapter optional), DC 9.0V		Height	14 in. (35.56 cm.)
Ports		Width	16.125 in.
6 Downstream/Upstream, 6 Downstream/Upstream		Depth	19.75 in.
Operating Temperature		Master Carton Qty.	24
20 to 50 degrees (Celsius) , 20 to 50 degrees (Celsius)		Weight	
Storage Temperature		Master Carton Wt.	37.78 lb.
0 to 70 degrees (Celsius), 0 to 70 degrees (Celsius)		Unit Pack Wt.	1.48 lb.
Operating System Support			
Win 98SE, 2000, ME, XP, MAC OS 8.6 or greater, Win 98SE, 2000, ME, XP, MAC OS 8.6 or greater			
FireWire Specification			
IEEE 1394a, IEEE 1394a			
Transfer Rate			
100, 200, 400 Mbps, 100, 200, 400 Mbps			
Humidity			
20-80% RH, (Non Condensing), 20-80% RH, (Non Condensing)			
Cable Length			
6 ft., (1.83 m.)			
Power Connections			
Bus or Self Powered, Bus or Self Powered			