

GHDMIS4W6

4-Port HD Audio/Video Switch with Remote, 4 HDMI Inputs - 1 HDMI Output



Provide additional HDMI connections to your HDTV – HDMI, Ultimate Viewing Experience Take your HDTV to the next level with HDMI technology, the new connectivity standard in digital consumer electronics, delivering the most vivid and richest viewing experience available today into your living room. High Definition Multimedia Interface (HDMI) technology is the latest digital interface that provides HD video and multi-channel audio through a single cable. IOGEAR's HDMI Switch enables you to connect multiple HD source devices to your HDTV for your viewing pleasure. It is an ideal solution for connecting multiple HD media devices such as...

- Video game consoles
- Media PCs, computers
- Set top boxes from cable and satellite providers
- DVRs, DVD players, AV receivers and many more...

Switching between Media Sources Select and view the desired source device at a push of a front panel pushbutton or the switch remote.

Provides User-Friendly Convenience No need to mess around with the TV's AV input selections. The switch eliminates the hassle of figuring out the correct AV input for the desired device.

- 4x HDMI inputs and 1x HDMI output
- HDMI v1.3b and HDCP Compliant
- Superior Resolution
 - HDTV: maintains 480p, 720p, 1080i, and 1080p resolution
 - PC Support: VGA, SVGA, XGA, SXGA, UXGA (1600 x 1200), and WQXGA (2560 x 1536)
- Switching port via remote control or front-panel pushbutton
- IR sensor up to 22.96 feet (7M)
- Front-panel LED for port and power status
- Backwards compatible with DVI devices with a DVI (male) to HDMI (female) adapter. IOGEAR HDMI/DVI adapter, GHDMIFDVIMW6.



Requirements

- HDTV or display with HDMI connections
- Digital media devices with HDMI connections

Package Contents

- 1 x 4-Port HDMI Switch
- 1 x Remote Control
- 1 x Full Range Power Adapter
- 1 x US Prong
- 1 x German Prong
- 1 x Quick Start Guide
- 1 x Warranty Card

Specifications

Function	GHDMIS4W6
Power	
Voltage	DC 6V
Amps	1A
Video Resolution	480p, 720p, 1080i, 1080p; 1920x1200
Video connections	
Input	HDMI
Output	HDMI
Connectors	
Video Input	4 x HDMI Type A 19 Pin Female
Video Output	1 x HDMI Type A 19 Pin Female
LEDs	
On Line	4
Power On	1
Computer Connections	
Daisy Chain or Cascading	Dependence on Signal Strength and Cable Distance
Environment	
Humidity	0-80% RH (Non Condensing)
Operation Temperature	32F~122F (0C~50C)
Storage Temperature	-4F~140F (-20C~60C)
Power Consumption	3watts (max)
Power Adapter	Universal Power Adapter 100~240 (50/60Hz)

Dimensions	GHDMIS4W6
Unit Dimensions	
Height	0.875in.
Depth	3.5in.
Width	6.438in.
Inner Pack	
Height	5.25in.
Length	9.25in.
Width	8.125in.
Inner Pack Qty.	3
Unit Package Dimensions	
Height	7.625in.
Width	4.75in.
Depth	3.875in.
Master Carton	
Height	10.125in.
Width	11.375in.
Depth	17.25in.
Master Carton Qty.	12
Weight	
Master Carton Wt.	14.6lb.
Inner Pack Wt.	3.2lb.
Unit Pack Wt.	1lb.
Unit Wt. w/accessories	0.6lb.
Unit Wt.	0.2lb.