

GHE125C

COMBO 2.5" ION? Drive Enclosure



Requirements

For PC users: Windows® 98SE, 2000, ME, XP Available FireWire or USB 2.0 port For MAC users: Mac OS X or greater (USB 2.0, USB 1.1, and FireWire) Mac OS 8.6 - 9.0 (USB 1.1 and FireWire) Available FireWire or USB 2.0 port

Package Contents

GHE125C - COMBO 2.5" Hi-Speed hard drive case 1 Premium FireWire cable (4-pin to 6-pin) 1 Premium USB 2.0 cable (Type mini-B to A) 1 Power adapter 1 Software CD 1 Manual 1 Registration/Warranty Card

Specifications

Function	GHE125C	Dimensions	GHE125C
Housing		Unit Dimensions	
Case	Metal	Height	0.6 in. (1.7 cm.)
Power Consumption		Length	6.4 in. (16.5 cm.)
Power Consumption	5.0V 2.1A	Width	3.1 in. (8.1cm.)
Ports		Unit Package Dimensions	
Ports	(1) Firewire 4-pin port / (1) USB mini-B port	Height	9.75 in. (24.7 cm.)
Operating Temperature		Width	2.5 in. (6.35 cm.)
Operating Temperature	68 ~ 122 ° F (20 ~ 50 ° C)	Depth	6.5 in. (16.5 cm.)
Storage Temperature		Master Carton	
Storage Temperature	32 ~ 158 ° F (0 ~ 70 ° C)	Height	10.5 in. (26.67 cm.)
Operating System Support		Width	17.75 in. (45.09 cm.)
Operating System Support	WIN 98SE, 2000, ME, XP, MAC OS 8.6 or greater	Depth	15.75 in. (40.01 cm.)
USB Specification		Master Carton Qty.	12
USB Specification	Firewire / USB 1.1 and 2.0 compliant	Weight	
Transfer Rate		Master Carton Wt.	22.70 lbs. (10.22 kg.)
Transfer Rate	400Mbps Firewire / 480 Mbps USB 2.0	Unit Pack Wt.	1.75 lbs. (.78 Kg.)
Humidity		Unit Wt.	.45 lbs. (.20 Kg.)
Humidity	20-80% RH, (Non Condensing)		
Cable Length			
Cable Length	Free Firewire & Hi-Speed USB 2.0 Cable (3 Feet Each)		
Power Connections			
Power Connections	Power Adapter (required)		