

GHE225U

2.5" Hi-Speed USB 2.0 ION? Drive Enclosure II



- USB 2.0 interface, supporting high speed data transfer rates of up to 480 Mbps
- Backward compatible with USB 1.1 specifications
- Fully compatible with IDE ATA-100 and ATA-5 & ATA-6 peripheral devices
- Hot swappable, Hot pluggable, Plug-n-Play
- Compact size, perfect for the mobile professional
- 1 Year Limited Warranty



Requirements

For PC users:

Windows® 98SE, 2000, ME, XP Available USB 2.0 or 1.1 port

For MAC users: Mac OS X or greater (USB 2.0 & USB 1.1) Mac OS 8.6 - 9.0 (USB 1.1) USB 2.0 or 1.1 port

** 12 mm drive not supported, only 9.5 mm standard drives are supported

Package Contents

- GHE225U - 2.5" Hi-Speed
- USB 2.0 ION drive case
- 1 Premium USB 2.0 cable (Type mini-B to A)
- 1 Software CD
- 1 Manual
- 1 Registration/Warranty Card

Specifications

Function	GHE225U	Dimensions	GHE225U
Housing		Unit Dimensions	
Case	Metal	Height	0.6 in. (1.7 cm.)
Power Consumption		Length	6.4 in. (16.5 cm.)
Ports	(1) USB mini-B port	Width	3.1 in. (8.1cm.)
Operating Temperature	68 ~ 122 ° F (20 ~ 50 ° C)	Unit Package Dimensions	
Storage Temperature	32 ~ 158 ° F (0 ~ 70 ° C)	Height	9.75 in. (24.7 cm.)
Operating System Support	WIN 98SE, 2000, ME, XP, MAC OS 8.6 or greater	Length	6.5 in. (16.5 cm.)
USB Specification	USB 1.1 and 2.0 compliant	Width	2.5 in. (6.35 cm.)
Transfer Rate	480 Mbps (USB 2.0)	Master Carton	
Humidity	20-80% RH, (Non Condensing)	Height	18 in. (45.72 cm.)
Cable Length	Hi-Speed USB 2.0 Cable (3 Feet)	Width	13.5 in. (34.29 cm.)
Power Connections	Power Adapter (Optional)	Depth	20.25 in. (51.44 cm.)
		Master Carton Qty.	12
		Weight	
		Master Carton Wt.	23.10 lbs. (10.4 Kg.)
		Unit Pack Wt.	1.75 lbs. (.78 Kg.)
		Unit Wt.	.45 lbs. (.20 Kg.)