

GHE425U

2.5" Hi-Speed USB 2.0 ION? Drive Enclosure III



- USB 2.0 interface, supporting high speed data transfer rates of up to 480 Mbps
- Backward compatible with USB 1.1 specifications
- Fully compatible with IDE ATA-100 and ATA-5 & ATA-6 peripheral devices
- Hot swappable, Hot pluggable, Plug-n-Play
- Compact size, perfect for the mobile professional
- 1 Year Limited Warranty



Requirements

For PC users:

- Windows® 2000, XP
- Available USB 2.0 or 1.1 port

For MAC users:

- Mac OS X version 10.4 or greater
- Available USB 2.0 or 1.1 port

Package Contents

- 1 GHE425U - 2.5" Hi-Speed USB 2.0 ION drive enclosure
- 1 Premium USB 2.0 cable (Type mini-B to A)
- 1 Quick Start Guide
- 1 Registration/Warranty Card

Specifications

Function	GHE425U	Dimensions	GHE425U
Housing		Unit Dimensions	
Case	Metal	Height	0.6 in. (1.7 cm)
Power Consumption	5.0V 2.1A	Length	5.0 in. (12.7 cm)
Ports	(1) USB mini-B port	Width	3.1 in. (8.1 cm)
Operating Temperature	68 ~ 122 ° F (20 ~ 50 ° C)	Unit Package Dimensions	
Storage Temperature	32 ~ 158 ° F (0 ~ 70 ° C)	Height	9.65 in. (24.5 cm)
Operating System Support	WIN 2000, XP, MAC OS X (10.2) or greater	Length	6.87 in. (17.45 cm)
USB Specification	USB 1.1 and 2.0 compliant	Width	2.5 in. (6.35 cm)
Transfer Rate	480 Mbps (USB 2.0)	Master Carton	
Humidity	20-80% RH, (Non Condensing)	Height	14.6 in. (37.1 cm)
Cable Length	Hi-Speed USB 2.0 Cable (1.5 Feet)	Width	10.83 in. (27.5 cm)
		Depth	16.14 in. (41.00 cm)
		Master Carton Qty.	12
		Weight	
		Master Carton Wt.	10.9 lbs (4.95 Kg)
		Unit Pack Wt.	0.9 lbs (0.41 Kg)
		Unit Wt.	0.4 lbs (0.18 Kg)