

GHSW8441

## True 4K 4-Port Switcher with HDMI® Connection

- Connect and switch between 4 HDMI® sources on 1 HDMI display
- True 4K resolutions to 4096 x 2160 @ 60Hz (4:4:4)
- Distribute uncompressed audio formats
- Flexible control via push-button, IR remote & RS-232 serial control
- Bi-directional RS-232 support for universal remotes & touch panels



### 4-Port True 4K Switch With HDMI®

The IOGEAR 4-Port True 4K Switch with HDMI connection offers smooth, quick switching between four HDMI video sources such as a computer, Blu-ray or media player, and cable or satellite receivers and a single HDMI display. Send crystal clear, Cinema 4K video reaching true 4K resolutions to 4096 x 2160 @ 60Hz with 4:4:4 Chroma subsampling, High Dynamic Range (HDR) and uncompressed audio for any variety of uses including home theater, in lobbies and conference rooms and for digital signage.


### Flexible Source Switching

Easily switch between each source automatically or manually. Utilize one of three Switch Modes and auto-cycle through your sources with smooth video transitions to display a variety of content. Manually switch between sources with the included IR remote control, or select a source via front panel push-buttons in settings where a remote control is not needed.

- Connect and switch between 4 HDMI® sources to 1 HDMI display
- True 4K resolutions to 4096 x 2160 @ 60Hz (4:4:4)
- Cascade up to 3 levels (64 source ports)
- Distribute uncompressed audio formats
- Flexible control via push-button, IR remote control
- Auto-Switch mode detects & selects new HDMI port connections
- Supports high-speed data rates up to 18 Gbps
- HDCP 2.2 Compliant
- CEC Compliant



Switch between four HDMI video sources such as a computer, Blu-ray or media player, and cable or satellite receivers and a single HDMI display



### Requirements

- HDMI source
- HDMI Display or projector

### Package Contents

- 1 x GHSW8441 4-Port 4K Switch with HDMI Connectors
- 1 x Power Adapter
- 1 x IR Remote Control Unit
- 1 x HDMI Cable
- 1 x User Manual
- 1 x Warranty Card

## Specifications

Function GHSW8441

#### Video connections

Input HDMI  
Output HDMI

#### Display Output

HDMI HDCP 2.2

#### Connectors

RS-232 1 x DB-9 Female

#### Environment

Humidity 0-80%  
Operation Temperature 32~104°F (0~40°C)  
Storage Temperature -4F ~ 140F (-20 - 60C)

#### Housing

Case Metal

Power Adapter 5V/2A

Power Consumption 5W

Video Resolution 4096 x 2160 @ 60Hz (4:4:4)

Video Streaming 18 Gbps (6Gbps per lane)

Warranty 3 - Years

Dimensions GHSW8441

#### Unit Dimensions

Height 0.98 in  
Length 7.87 in  
Depth 3.23 in

#### Unit Package Dimensions

Height 9.40 in  
Length 6.30 in  
Depth 2.32 in

#### Master Carton

Height 10.04 in  
Width 14.89 in  
Depth 7.17 in  
Master Carton Qty. 6

#### Weight

Master Carton Wt. 11.55 lb

#### Physical Properties

Unit Weight 1.03 lb  
Unit Weight with package 1.83 lb