

GHSW8441

# True 4K 4-Port Switcher with HDMI Connection



- Connect and switch between 4 HDMI® sources on 1 HDMI display
- True 4K resolutions to 4096 x 2160 @ 60Hz (4:4:4)
- Distribute uncompressed audio formats
- Flexible control via push-button, IR remote & RS-232 serial control
- Bi-directional RS-232 support for universal remotes & touch panels

## 4-Port True 4K Switch With HDMI®

The IOGEAR 4-Port True 4K Switch with HDMI connection offers smooth, quick switching between four HDMI video sources such as a computer, Blu-ray or media player, and cable or satellite receivers and a single HDMI display. Send crystal clear, Cinema 4K video reaching true 4K resolutions to 4096 x 2160 @ 60Hz with 4:4:4 Chroma subsampling, High Dynamic Range (HDR) and uncompressed audio for any variety of uses including home theater, in lobbies and conference rooms and for digital signage.


## Flexible Source Switching

Easily switch between each source automatically or manually. Utilize one of three Switch Modes and auto-cycle through your sources with smooth video transitions to display a variety of content. Manually switch between sources with the included IR remote control, or select a source via front panel push-buttons in settings where a remote control is not needed.

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Connect and switch between 4 HDMI® sources on 1 HDMI display</li> <li>• True 4K resolutions to 4096 x 2160 @ 60Hz (4:4:4)</li> <li>• Cascade up to 3 levels (64 source ports)</li> <li>• Distribute uncompressed audio formats</li> </ul> | <ul style="list-style-type: none"> <li>• Flexible control via push-button, IR remote control</li> <li>• Auto-Switch mode detects &amp; selects new HDMI port connections</li> <li>• Supports high-speed data rates up to 18 Gbps</li> <li>• No-slip locking power supply mechanism</li> <li>• HDCP 2.2 Compliant</li> <li>• CEC Compliant</li> </ul> |
|--|--|



Switch between four HDMI video sources such as a computer, Blu-ray or media player, and cable or satellite receivers and a single HDMI display



### Requirements

- HDMI source
- HDMI Display or projector

### Package Contents

- 1 x GHSW8441 4-Port 4K Switch with HDMI Connectors
- 1 x Power Adapter
- 1 x IR Remote Control Unit
- 1 x HDMI Cable
- 1 x User Manual
- 1 x Warranty Card

## Specifications

Function	GHSW8441	Dimensions	GHSW8441
<b>Video connections</b>		<b>Unit Dimensions</b>	
Input	HDMI	Height	0.98 in
Output	HDMI	Depth	3.23 in
<b>Display Output</b>		Length	7.87 in
HDMI	HDCP 2.2	<b>Unit Package Dimensions</b>	
<b>Connectors</b>		Height	9.40 in
RS-232	1 x DB-9 Female	Depth	2.32 in
<b>Environment</b>		Length	6.30 in
Humidity	0-80%	<b>Master Carton</b>	
Operation Temperature	32~104°F (0~40°C)	Width	14.89 in
Storage Temperature	-4F ~ 140F (-20 - 60C)	Height	10.04 in
<b>Housing</b>		Depth	7.17 in
Case	Metal	Master Carton Qty.	6
<b>Power Adapter</b>		<b>Weight</b>	
Power Adapter	5V/2A	Master Carton Wt.	11.55 lb
<b>Power Consumption</b>		<b>Physical Properties</b>	
Power Consumption	5W	Unit Weight	1.03 lb
<b>Video Resolution</b>		Unit Weight with package	1.83 lb
Video Resolution	4096 x 2160 @ 60Hz (4:4:4)		
<b>Video Streaming</b>			
Video Streaming	18 Gbps (6Gbps per lane)		
<b>Warranty</b>			
Warranty	3 - Years		