

GHSW8481

True 4K 8-Port Switcher with HDMI® connection (TAA Compliant)



- Connect and switch between 8 HDMI sources on 1 HDMI display
- True 4K resolutions to 4096 x 2160 @ 60Hz (4:4:4)
- · Distribute uncompressed audio formats
- Flexible control via push-button, IR remote & RS-232 serial control
- Bi-directional RS-232 support for universal remotes & touch panels

- Connect and switch between 8 HDMI sources on 1 HDMI display
- True 4K resolutions to 4096 x 2160 @ 60Hz (4:4:4)
- HDMI (3D, 12-Bit Deep Color, 4K); HDCP 2.2 compliant
- Supports HDR10+; distributes uncompressed audio formats
- Cascade up to 3 levels (512 source ports)


- Flexible control via push-button, IR remote & RS-232 serial control
- Bi-directional RS-232 support for universal remotes & touch panels
- Auto-switch mode detects & selects new HDMI port connections
- Supports high-speed data rates up to 18 Gbps
- No-slip locking power supply mechanism
- CEC compliant
- Plug-n-Play











Requirements

Package Contents

- Up to 8 HDMI source Devices
- 1 HDMI Display or Projector
- 1 x GHSW8481 8-Port True 4K Video Switch
- 1 x IR Remote Control
- 1 x IR Extension Cable
- 1 x Power Adapter
- 1 x Rack Mounting Kit
- 1 x Quick Start Guide
- 1 x Warranty Card

Specifications

Function	GHSW8481	Dimensions	GHSW8481
Switches		Unit Dimensions	
DIP	1 x Auto Switch On/Off	Height	1.75 in
Video connections		Length	17.25 in
Input	8 x HDMI Type A Female	Depth	6.25 in
Output	1 x HDMI Type A Female	Unit Package Dimensions	
Cable Length	Maximum of 9.84 Feet	Height	9.25 in
Video Performance		Length	21.25 in
Local	HDCP 2.2 with CEC support	Depth	4.50 in
Video Resolution	4096 x 2160 @ 60Hz (4:4:4)	Master Carton	
Connectors		Height	
RS-232	Connector: 1 x DB-9 Female (Black)	Width	
Power	1 x DC Jack with locking barrel	Depth	
Power Adapter	5.3 VDC/1A	Master Carton Qty.	3
Power Consumption	3.73 W	Weight	
Transmission Power	Max. Data Rate 18 Gbsp	Master Carton Wt.	
Operating Temperature	32~104°F (0~40°C)	Unit Pack Wt.	5.70 lb
Storage Temperature	-4F ~ 140F (-20 - 60C)	Unit Wt.	3.95 lb
Environment			
Humidity	0 - 80% RH, Non-Condensing		