

GIC250U Hi-Speed USB 2.0 PCI Card

IOGEAR brings you the first five-port USB 2.0 PCI Card (GIC250U). USB 2.0 moves data at a blazing rate of 480 Mbps (Megabits per second), and is fully backward compatible with the first generation of USB devices. With the increase in speed, USB 2.0 offers enhanced functionality, allowing more devices to share the increased bandwidth. The new USB 2.0 PCI card will allow you to take full advantage of the USB 2.0 technology on your current USB 1.1 systems.

- 40 times faster than USB 1.1
- Supports high speed data transfer rates of up to 480 Mbps
- Supports Mac OS 8.6 or greater. Requires Mac OS X for USB 2.0 support;
- Windows® 98, 98SE, 2000, ME, XP

- 1 Internal Type A USB Port
- 4 External Type A USB Ports
- Hot Swappable Plug-n-Play
- Fully backwards compatible with USB 1.1

Last Last Last

- PC Power Management v2.2 compliant
- 3 Year Limited Warranty





Requirements

For PC Users

- Windows® 98, 98SE, 2000, ME, XP
- Available PCI Slot

For MAC Users

- Mac 8.6 or greater. Requires OS X for USB 2.0 support
- Available PCI Slot

Function	GIC250U	Dimensions	GIC250U
Ports	4 external downstream, 1 internal downstream	Unit Dimensions	
Operating Temperature	20 to 50 degrees (Celsius)	Height	4.75 in. (12 cm.)
Storage Temperature	0 to 70 degrees (Celsius)	Depth	0.91 in. (2.3 cm.)
Operating System Support	Windows?98, 98SE, 2000, ME, XP, MAC OS 8.6 or greater; Mac OS X required for USB 2.0 support	Width	5.25 in. (13.3 cm.)
		Unit Package Dimensions	
USB Specification	USB 1.1 and 2.0 compliant	Height	6.5 in. (16.5 cm.)
Transfer Rate		Width	9.5 in. (24.1 cm.)
I ranster kate	480 Mbps	Depth	2.5 in. (6.4 cm.)
Humidity	20-80% RH, (Non Condensing)	Master Carton	
		Height	13.75 in. (34.93 cm.)
		Width	16.0 in. (40.64 cm.)
		Depth	19.75 in. (50.17 cm.)
		Master Carton Qty.	24
		Weight	
		Master Carton Wt.	19.75 lbs. (8.89 kg.)

Unit Pack Wt.

1.5 lbs. (0.675 kg.)

Specifications

Package Contents

- GIC250U 5 Port USB 2.0 PCI Card
- Warranty Card
- Instruction sheet
- Installation CD