

GIC3U2

2-Port SuperSpeed+ (10Gbps) USB-A PCI- Express Card (TAA Compliant)



2-Port SuperSpeed+ (10Gbps) USB-A PCI-Express Card

IOGEAR's TAA Compliant GIC3U2 2-port USB-A PCI Express card adds USB 3.1 (gen2) Type-A ports to your computer. The high performance expansion card includes a low-profile bracket and features efficient construction that fits into any x4, x8 and x16 PCIe slot. This PCIe card instantly upgrades your computer by equipping it with a lightning fast data transfer rate of 10Gbps, that's twice the speed of USB 3.0 (5Gbps) and almost 20 times that of USB 2.0 (480Mbps). Each USB port supplies a maximum power output of 5V/3A to fast-charge your devices. The card is fully compliant with USB 3.1 Specification Revision 1.0 and PCI Express Specification 3.0. With more bus bandwidth and high performance capabilities, this expansion card is perfect for transferring and accessing data with external hard drives, and other high bandwidth USB 3.1 peripherals.

Cost Effective Backwards Compatibility

The versatility of the 2-Port USB-A PCI-Express Card makes it a cost effective solution. The USB 3.1 PCIe is backwards compatible with USB 3.0, USB 2.0, and USB 1.1 so you can stay connected to legacy USB devices and avoid the hassle and high cost of purchasing new peripherals. It is also compatible with PCI Express 1.1, 2.0, and 3.0 specifications. For added functionality, pair the PCIe card with the [G2LU3CAM01-WT](#) USB-C to USB-A cable to connect your USB-C devices.

- Add two USB Type-A ports to your desktop computer
- USB 3.1 PCIe physical x4 Lane Host Adapter
- Two USB 3.1 Type-A downstream connectors on board
- Supports data transfer speed of up to 10Gbps
- Compliant with USB 3.1 Specification Revision 1.0
- Compliant with PCI Express Specification 3.1
- Each USB port supplies maximum 5V/3A power output
- Cost effective backwards compatibility
- TAA Compliant



Requirements

- Windows® 7, Windows® 8, Windows® 8.1, Windows® 10
- Available PCIe x4, x8, or x16 slot

Package Contents

- 1 x GIC3U2
- 1 x Low-profile bracket
- 1 x Quick Start Guide
- 1 x Warranty Card

Specifications

Function	GIC3U2	Dimensions	GIC3U2
USB Specification	USB 3.1 Gen 2	Unit Dimensions	
Ports	2 USB-A Female Ports	Height	4.8125 inch (12.22 cm)
Data Rate	Supports data transfer rate upto to Superspeed+(10Gbps)	Depth	0.75 inch (1.905 cm)
Computer Interface	PCI Express x4, x8, or x16 slot	Length	3.6875 inch (9.366 cm)
Connectors (Console)	2 x USB Type-A (F) downstream	Inner Pack	
Operating System Support	Windows 7, Windows 8, Windows 8.1, Windows 10 (32/64-Bit)	Width	8.25 inch (20.96 cm)
Operating Temperature	32°F ~ 134.6°F (0°C ~ 57°C)	Height	7.375 inch (18.73 cm)
Storage Temperature	-4°F ~ 185°F (-20°C ~ 85°C)	Length	6.25 inch (15.875 cm)
Power Connections	15-Pin SATA power connector	Inner Pack Qty.	6
		Unit Package Dimensions	
		Width	6.875 inch (17.46 cm)
		Height	5.625 inch (14.287 cm)
		Depth	1.25 inch (3.175 cm)
		Master Carton	
		Width	17.5 inch (44.45 cm)
		Height	8.5 inch (21.60 cm)
		Depth	12.875 inch (32.70 cm)
		Master Carton Qty.	24
		Weight	
		Master Carton Wt.	9.5 lb (4.3 kgs)
		Inner Pack Wt.	1.95 lb (0.88 kgs)
		Unit Pack Wt.	0.3 lb (0.12 kgs)
		Unit Wt.	0.1 lb (0.04 kgs)