

GPF113

3-Port FireWire? CardBus Card



- Three 6-pin FireWire? connectors to daisy chain up to 63 devices simultaneously
- Automatic configuration and no drivers required

- Supports 100/200/400 Mbps serial throughput
- IEEE 1394 & 1394 OHCI v 1.0 compliant, 1394A v2.0 compliant
- Hot swappable, Plug-n-Play
- Easy installation



Requirements

For PC Users

- Windows®98SE, 2000, ME, XP
- Available CardBus Slot

For MAC Users

- Mac OS 10.2 or greater
- Available Cardbus Slot

Package Contents

- GPF113 - IEEE 1394 PCMCIA Card
- Warranty Registration Card
- Users Manual

Specifications

Function	GPF113	Dimensions	GPF113
Housing		Unit Package Dimensions	
Case	Metal/Plastic	Height	6.5 in. (16.5 cm.)
Ports	(3) FireWire 1394a	Width	9.5 in. (24.1 cm.)
Operating Temperature	20 to 50 degrees (Celsius)	Depth	2.5 in. (6.4 cm.)
Storage Temperature	0 to 70 degrees (Celsius)	Master Carton	
Operating System Support	Windows98SE, 2000, ME, XP, MAC OS 10.2 or greater	Height	10.5 in. (26.67 cm.)
FireWire Specification	IEEE 1394a	Width	10.25 in. (26.03 cm.)
Transfer Rate	400 Mbps	Depth	20 in. (50.8 cm.)
Humidity	20-80% RH, (Non Condensing)	Master Carton Qty.	12
Power Connections	CardBus Slot	Weight	
		Master Carton Wt.	5.9 lbs. (2.66 Kg.)
		Unit Pack Wt.	11.3 Oz. (320 g.)
		Unit Wt.	2 oz. (56.8 g.)