

GPSR01U Wireless USB Print Server, 1-port

- Easily connect your USB printer to a wireless network
- Allows multiple computers to share one USB printer on the wireless
 network
- Print from any computer on your network or from across the Internet
- Supports DHCP Client and multiple network protocols
- Works with 802.11b or 802.11g wireless networks
- Data transfer rate up to 11Mbps
- Up to 150ft indoor range and 500ft outdoor range
- Supports Telnet and Web Management software





Requirements

Operating Systems:

- Windows 98SE/ME/NT/2000/XP
- Novell(iBindery/NDS)
- Mac OS 8.6 or Later (only supports post-script printers)*
 Unix/Linux

The print server only supports post-script printers under Mac OS 8.6 or later

Printers:

- · Most printers with USB connections are supported
- · Limited support on multi-function printers

Network environment:

• 802.11b or 802.11g Wireless networks

Specifications

Function	GPSR01U	Dimensions	GPSR01U
Operating Temperature	0 - 50 C	Unit Dimensions	
Storage Temperature	-5 - 65 C	Height	1 in. (2.54 cm.)
Humidity	Operating 0 - 70%; Storage 0 - 80%	Length	2.5 in. (5.72 cm.)
Power Connections	3.3V, 2A	Width	2.4 in. (6.096 cm.)
Network Protocol	TCP/IP, IPX, BetBEUI, Appletalk, LPR	Unit Package Dimensions	
Data Rate	Up to 11 Mbps (11 Mbps, 5.5 Mbps, 2 Mbps, 1 Mbps.)	Height	5 in.
Network Interface	802.11b	Width	8 in.
Printer Connection	USB 1.1	Depth	2.75 in. (6.99 cm.)
Standards	802.11b Compliant	Master Carton	
Management	1. Web Interface 2. Window based Setup	Height	14 in. (35.56 cm.)
	Program	Width	8.5 in. (34.53 cm.)
RAM	2 MB	Depth	18 in. (45.72 cm.)
Radio Frequency	2.4 GHz ISM Band	Master Carton Qty.	12
Antenna Type	Internal, PIFA Type (Peak Gain: 2)	Weight	
Flash Memory	1 MB	Master Carton Wt.	13.2 Lbs. (6.0 kg.)
System Memory	2 MB SDRAM	Unit Pack Wt.	1 lb.
		Unit Wt.	1.12 lbs. (0.5 kg.)

• 1 Wireless USB Print Server

• 1 User manual

Package Contents

- 1 Installation CD
- 1 Warranty/registration card
- 1 Power adapter