

GUC100KM

USB Adapter



- No software required
- Can be used in conjunction with MiniView series PS/2 KVM switches to control PS/2 & USB computers with a single keyboard, mouse and monitor
- Two PS/2 devices (Keyboard and Mouse) to USB Interface Converter
- Supports PS/2 mice and Microsoft IntelliMouse
- Supports Windows 98/98SE/Me/2000/XP; Apple Macintosh G3/G4/G5/iMac/eMac systems w/OS 8.6 or higher; Sun Blade servers 2000/100 (Sun Solaris 8); Linux; OS/2 Warp 4.51 or higher
- Remote wake up function
- USB 1.0 and 1.1 specification compliant
- Easy installation - No software required
- USB Bus powered - External power adapter not required
- Compatible with KVM devices



Requirements

Package Contents

For PC Users

- Windows® 98, 98SE, 2000, ME, XP
- Available USB port

- USB to PS/2 adapter for keyboard/mouse
- Users Manual
- Warranty/Registration Card

For MAC Users

- Mac OS 8.6 or higher
- Available USB port

For SUN Users

- Sun Blade servers 2000/100 (Sun Solaris 8)
- Available USB port

For Linux Users

- Latest USB supporting Linux OS
- Available USB port

Other

- OS/2 Warp 4.51 or higher
- Available USB port

Specifications

Function	GUC100KM	Dimensions	GUC100KM
Housing		Unit Package Dimensions	
Case	Plastic	Height	5 in.
Ports	(2) PS/2	Width	4.875 in.
Operating Temperature	20 to 50 degrees (Celsius)	Depth	1.675 in.
Storage Temperature	0 to 70 degrees (Celsius)	Master Carton	
Operating System Support	Win 98, 98SE, 2000, ME, XP, MAC OS 8.6 or greater. SUN Solaris 8	Height	8.25 in. (20.96 cm.)
USB Specification	USB 1.1 compliant	Width	11 in. (27.94 cm.)
Transfer Rate	12 Mbps	Depth	15.75 in. (40 cm.)
Humidity	20-80% RH, (Non Condensing)	Master Carton Qty.	24
Cable Length	6 in. (15.24 cm.)	Weight	
Power Connections	Bus powered	Master Carton Wt.	9.4 lbs. (4.27 kg.)
		Unit Pack Wt.	0.28 lb.
		Unit Wt.	0.30 lbs. (0.135 kg.)