

GUC2015V

USB 2.0 External VGA Video Card



USB to VGA - External USB 2.0 to VGA Video Card

The IOGEAR's USB 2.0 External VGA Video Card allows you to easily connect an extra monitor to your desktop or laptop's USB port for a seamless dual display set up. The connected monitor can be configured to either mirror your primary screen, or extend it across an additional display allowing visibility of more applications at the same time. The USB to VGA video card includes specialized software that is easy to install and guarantees little difference in performance between a directly connected screen and a screen connected through the USB 2.0 External VGA Video Card.

- Easily connect additional VGA monitors via USB 2.0 ports
 - Extend your desktop, or mirror content on two displays
 - Add up to six* external VGA video cards via USB 2.0 ports
 - Support resolutions of up to 1280 x 1024 at 32-bit color
 - No need to open cases. Great for laptops or leasing computers
 - Bus Powered - No external power supply needed
 - Supports usage through powered KVMP's or USB hubs
- Office Use:
 - View large spreadsheets across two screens with display continuity
 - Multitask more effectively without overlapping windows
 - Open attachments on one screen while reading the e-mail on the other
 - Graphic Use:
 - Use second display for palettes & tools
 - Data Entry Use:
 - Type documents on one screen while viewing reference material on the other
 - Wall Street:
 - Use a notebook for viewing multiple screens
 - View charts and live data at the same time

*Requires six USB 2.0 ports. Not recommended to connect with USB hubs. The possibilities with the IOGEAR DVI display adapter are endless.



How does it work?



Requirements

- Windows® 8.1 (32-bit / 64-bit), Windows® 8 (32-bit / 64-bit), Windows® 7 (32-bit / 64-bit), Windows Vista®, Windows XP®
- Intel based Mac OS X 10.4 and above
- Available USB 2.0 port (not compatible with USB 1.x)

Package Contents

- 1 - USB to SXGA Adapter
- 1 - Quick Start Guide
- 1 - Driver CD
- 1- 4ft USB 2.0 Cable

Specifications

Function	GUC2015V
Power Consumption	5V
Video Resolution	1280 x 1024
Ports	1 Female VGA / 1 USB 2.0 Type mini-B
Operating Temperature	32 ~ 122 ° F (0 ~ 50 ° C)
Storage Temperature	14 ~ 158 ° F (-10 ~ 70 ° C)
Operating System Support	Windows XP®, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Apple Mac OS X 10.4/10.5/10.6.10.7 (Intel-based)
USB Specification	2.0 compliant
Humidity	10-90% RH, (Non Condensing)
Power Connections	Optional Power Port
Connectors	
USB	1
Video Output	1
Color Depth	32-bit true color

Dimensions	GUC2015V
Unit Dimensions	
Height	2.3 Inch
Length	3.375 Inch
Width	0.75 Inch
Inner Pack	
Height	17 in. (43 cm)
Length	7 in. (17.8 cm)
Width	16.5 in. (42 cm)
Inner Pack Qty.	12
Unit Package Dimensions	
Height	7.9 in (20 cm)
Width	7.9 in (20 cm)
Depth	2 in. (5.1 cm)
Master Carton	
Height	17.72 in (45 cm)
Width	17.13 in (43.5 cm)
Depth	15.16 in (38.5 cm)
Master Carton Qty.	24
Weight	
Master Carton Wt.	19 lbs.
Unit Pack Wt.	0.75 lb
Unit Wt.	0.25 lb