

GUC2015VW6

# USB 2.0 External VGA Video Card Multi-Language Version



The USB 2.0 External VGA Video Card allows you to connect an extra monitor to your desktop PC or laptop's USB port. The connected monitor can be configured to either clone your primary screen, or extend the Windows desktop allowing visibility of more applications at the same time.

The USB 2.0 External Video Card driver used to control the extra screen uses very little computer resource and offers a vast array of screen resolutions and color depths. This ensures that there is little difference in performance between a directly connected screen and a screen connected through the USB 2.0 External Video Card

Ships with User Guide in English, French & Spanish.

- **Office Use:**
  - View large spreadsheets across two screens with display continuity
  - Multitask more effectively without overlapping windows
  - Open attachments on one screen while reading the e-mail on the other
- **Mobile Use:**
  - Do multiple screen displays and presentations without bringing another computer
- **Graphic Use:**
  - Use second display for pallets/tools
- **Data Entry Use:**
  - Type documents on one screen while viewing reference material on the other
- **Wall Street:**
  - Use a notebook for viewing multiple screens
  - View charts and live data at the same time
- **Entertainment:**
  - View videos/TV on one screen and your desktop on the other screen
- **Features:**
  - Easily connect additional monitors using a USB 2.0 Cable
  - Enjoy resolutions of up to 1280 x 1024 at 24 bit color
  - Allows for effortless multitasking
  - Bus Powered - No external power supply needed
  - Supports usage through powered KVMP's or USB hubs



## How does it work?



## Requirements

- Windows XP, Windows Vista, Windows 7 32-/64-bit, Windows 8/8.1 32-/64-bit
- Intel based Mac OS X 10.4 and above
- Available USB 2.0 port (not compatible with USB 1.x)

## Package Contents

- 1 x USB to SXGA Adapter
- 3 x Quick Start Guide (English, Spanish, French)
- 1 x Driver CD
- 1 x 4ft USB 2.0 Cable

## Specifications

Function	GUC2015VW6
<b>Power Consumption</b>	5V
<b>Video Resolution</b>	1280 x 1024
<b>Ports</b>	1 Female VGA / 1 USB 2.0 Type mini-B
<b>Operating Temperature</b>	32 ~ 122 ° F ( 0 ~ 50 ° C)
<b>Storage Temperature</b>	14 ~ 158 ° F ( -10 ~ 70 ° C)
<b>Operating System Support</b>	Windows XP®, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Apple Mac OS X 10.4/10.5/10.6.10.7 (Intel-based)
<b>USB Specification</b>	2.0 compliant
<b>Humidity</b>	10-90% RH, (Non Condensing)
<b>Power Connections</b>	Optional Power Port
<b>Connectors</b>	
USB	1
Video Output	1
<b>Color Depth</b>	32-bit true color

Dimensions	GUC2015VW6
<b>Inner Pack</b>	
Height	17 in.
Length	7 in.
Width	16.5 in.
Inner Pack Qty.	12
<b>Unit Package Dimensions</b>	
Height	6.5 in
Length	6.25 in
Width	2 in
<b>Master Carton</b>	
Height	14.13 in
Width	15.16 in
Depth	15.08 in
Master Carton Qty.	24
<b>Weight</b>	
Master Carton Wt.	19 lbs.
Unit Pack Wt.	.75 lbs