

GUC2020DW6

USB 2.0 External DVI Video Card



External USB 2.0 to DVI Video Card

The IOGEAR USB 2.0 External DVI Video Card instantly adds an additional high resolution DVI display through your USB 2.0 port. Simply install the driver, plug the adapter into the USB 2.0 port and you're ready to go.

Extend your Desktop for Increased Productivity

Extend your desktop across both displays allowing you to increase your productivity like never before. While reading email on one display, open attachments on the other display. Expand spreadsheets across both monitors; in graphics programs you can increase your working area by putting all your pallets on the second display.

Easily connect additional DVI monitors via USB 2.0 ports
Extend your desktop, or mirror content on two displays
Add up to six* external DVI video cards via USB 2.0 ports
Support resolution of UXGA 1600 x 1200 or HD 1920 x 1080 and 32-bit color
No need to open cases. Great for laptops or leasing computers

*Requires six USB 2.0 ports. Not recommended to connect with USB hubs.

The possibilities with the IOGEAR DVI display adapter are endless.

Office Use:

- View large spreadsheets across two screens with display continuity



Requirements

- Windows® 10, Windows® 8.1, Windows® 8, Windows® 7, Windows Vista® , Windows XP®
- Intel based Mac OS X 10.4 and above
- Available USB 2.0 port (not compatible with USB 1.x)
- DVI monitor or VGA monitor with DVI to VGA adapter

Package Contents

- 1 - USB to DVI Adapter
- 1 - DVI to VGA Adapter
- 1 - Quick Start Guide
- 1 - CD-ROM with User Guide and Installation Software
- 1 - 4 ft. USB 2.0 Cable

Specifications

Function	GUC2020DW6	Dimensions	GUC2020DW6
Power Consumption	5V	Unit Dimensions	
Video Resolution	Max 1920 x 1080	Height	0.8 in
Ports	1 Female DVI / 1 USB 2.0 Type mini-B	Length	3.5 in
Operating Temperature	68 ~ 122 °F (20 ~ 50 °C)	Width	2.25 in
Storage Temperature	32 ~ 158 °F (0 ~ 70 °C)	Inner Pack	
Operating System Support	Windows XP, Windows Vista, Windows 7, Mac OS X v10.4 or later	Height	17 in. (43 cm)
USB Specification	2.0 compliant	Length	7 in. (17.8 cm)
Humidity	20-80% RH, (Non Condensing)	Width	16.5 in. (42 cm)
Power Switch	Bus Powered	Inner Pack Qty.	12
Video connections		Unit Package Dimensions	
Input	USB	Height	7.9 in (20 cm)
Output	DVI	Width	7.9 in (20 cm)
Connectors		Depth	2 in. (5.1 cm)
USB	1	Master Carton	
Video Output	1	Height	17.72 in (45 cm)
Power Mode	USB	Width	17.13 in (43.5 cm)
Color Depth	32-bit true color	Depth	15.16 in (38.5 cm)
		Master Carton Qty.	24
		Weight	
		Master Carton Wt.	19 lbs.
		Inner Pack Wt.	9.4 lb
		Unit Pack Wt.	.8 lbs
		Unit Wt. w/accessories	0.35 lb
		Unit Wt.	0.25 lb