

GUC2020DW6

## USB 2.0 External DVI Video Card



### External USB 2.0 to DVI Video Card

The IOGEAR USB 2.0 External DVI Video Card instantly adds an additional high resolution DVI display through your USB 2.0 port. Simply install the driver, plug the adapter into the USB 2.0 port and you're ready to go.

### Extend your Desktop for Increased Productivity

Extend your desktop across both displays allowing you to increase your productivity like never before. While reading email on one display, open attachments on the other display. Expand spreadsheets across both monitors; in graphics programs you can increase your working area by putting all your pallets on the second display.

Easily connect additional DVI monitors via USB 2.0 ports  
 Extend your desktop, or mirror content on two displays  
 Add up to six\* external DVI video cards via USB 2.0 ports  
 Support resolution of UXGA 1600 x 1200 or HD 1920 x 1080 and 32-bit color  
 No need to open cases. Great for laptops or leasing computers

\*Requires six USB 2.0 ports. Not recommended to connect with USB hubs.

The possibilities with the IOGEAR DVI display adapter are endless.

#### Office Use:

- View large spreadsheets across two screens with display continuity



## Requirements

- Windows® 10, Windows® 8.1, Windows® 8, Windows® 7, Windows Vista®, Windows XP®
- Intel based Mac OS X 10.4 and above
- Available USB 2.0 port (not compatible with USB 1.x)
- DVI monitor or VGA monitor with DVI to VGA adapter

## Package Contents

- 1 - USB to DVI Adapter
- 1 - DVI to VGA Adapter
- 1 - Quick Start Guide
- 1 - CD-ROM with User Guide and Installation Software
- 1 - 4 ft. USB 2.0 Cable

## Specifications

Function	GUC2020DW6	Dimensions	GUC2020DW6
<b>Power Consumption</b>	5V	<b>Unit Dimensions</b>	
<b>Video Resolution</b>	Max 1920 x 1080	Height	0.8 in
<b>Ports</b>	1 Female DVI / 1 USB 2.0 Type mini-B	Length	3.5 in
<b>Operating Temperature</b>	68 ~ 122 °F ( 20 ~ 50 °C)	Width	2.25 in
<b>Storage Temperature</b>	32 ~ 158 °F ( 0 ~ 70 °C)	<b>Inner Pack</b>	
<b>Operating System Support</b>	Windows XP, Windows Vista, Windows 7, Mac OS X v10.4 or later	Height	17 in. (43 cm)
<b>USB Specification</b>	2.0 compliant	Length	7 in. (17.8 cm)
<b>Humidity</b>	20-80% RH, (Non Condensing)	Width	16.5 in. (42 cm)
<b>Power Switch</b>	Bus Powered	Inner Pack Qty.	12
<b>Video connections</b>		<b>Unit Package Dimensions</b>	
Input	USB	Height	7.9 in (20 cm)
Output	DVI	Width	7.9 in (20 cm)
<b>Connectors</b>		Depth	2 in. (5.1 cm)
USB	1	<b>Master Carton</b>	
Video Output	1	Height	17.72 in (45 cm)
<b>Power Mode</b>	USB	Width	17.13 in (43.5 cm)
<b>Color Depth</b>	32-bit true color	Depth	15.16 in (38.5 cm)
		Master Carton Qty.	24
		<b>Weight</b>	
		Master Carton Wt.	19 lbs.
		Inner Pack Wt.	9.4 lb
		Unit Pack Wt.	.8 lbs
		Unit Wt. w/accessories	0.35 lb
		Unit Wt.	0.25 lb