

GUC2322

USB to 2-port Serial RS-232 Converter



The IOGEAR USB to 2-port Serial RS-232 Converter provides two RS-232 serial connectors via one single USB port. You can instantly enjoy connectivity with modem, PDA, POS, and other serial devices on your PC or Mac without the hassle of opening your computer case. It provides a quick, simple, and cost-effective solution and is ideal for various communication and automation applications. The sturdy aluminum case with detachable USB cable design fits your commercial use or everyday connectivity needs.

- Two High-Speed RS-232 DB-9 male connectors support data rates up to 230 kbps, twice the speed of a standard PC serial port
- Dual data buffers for each upstream and downstream data transfer to ensure performance
- Slim aluminum design for durability & portability
- Detachable USB cable to fit any specific applications
- No external power adapter required
- LED indicators for adapter status and data activity
- Automatic IRQ and I/O Address Selection
- Two 16C450/16C550 Compatible UARTs
- Supports Transmit-Receive FIFO at 512 bytes per port
- Fully compliant with USB 2.0 & USB 1.1
- Supports power management and automatic handshake mode
- Supports hot-swapping and plug-and-play



Requirements

Package Contents

For PC Users

- Windows® 2000, Server 2003, XP*, Vista (32-bit/64-bit)
- Available USB port

**Vista driver supports both XP & Vista*

- 1 x USB to Serial adapter
- 1 x USB Cable
- 1 x Quick Start Guide
- 1 x Installation CD

For MAC Users

- Mac OS 10.3.9 and up
- Available USB port

Specifications

Function	GUC2322	Dimensions	GUC2322
Housing		POP Information	
Case	Aluminum	10" Peg Hook	6
LEDs		6" Peg Hook	4
Power On	1 (Orange)	Unit Dimensions	
Port Status	2 (Green)	Height	1 inch
Power Consumption		Depth	2.24 inch
USB Specification		Width	4.51 inch
Data Rate		Inner Pack	
Connectors		Height	7.25 inch
USB	1 x USB Type B Female	Length	5.5 inch
Serial	2 x DB-9 male	Width	13.25 inch
Environment		Inner Pack Qty.	6
Operation Temperature	0 to 55 degree C ; 32 to 130 degree F	Unit Package Dimensions	
Storage Temperature	0 to 70 degree C ; 32 to 155 degree F	Height	8.25 inch
Humidity	20% - 80% RH, Non-condensing	Width	6.125 inch
Device Connection		Depth	1.5 inch
RS-232 Signal		Master Carton	
Data Bit		Height	11.5 inch
Stop Bit		Width	16 inch
Power Mode		Depth	7.75 inch
Transmit - Receive FIFO		Master Carton Qty.	12
Power Management		Weight	
		Master Carton Wt.	10 lb
		Inner Pack Wt.	4.4 lb
		Unit Pack Wt.	0.75 lb
		Unit Wt. w/accessories	0.6 lb
		Unit Wt.	0.5 lb