

GUD3C11

# USB-C Triple Video Docking Station with 120 Watt Power Supply (TAA Compliant)



- Dock and expand your USB-C laptop with 11 port options
- Connect up to 3 HD 4K displays via 2 DisplayPorts, 1 HDMI port\*
- Keep your laptop charged with up to 60W Power Delivery
- 2x DisplayPort++ 1.2 ports support dual displays to 4K @ 60Hz
- 1x HDMI port with DP Alt Mode supports HD display to 4K @ 30Hz

## Triple Video USB-C Docking Station Packed With Features

IOGEAR TAA Compliant USB-C Triple Video Docking Station is designed to transform your USB-C laptop into a full-featured workstation that rivals a desktop. The Dock is equipped with 11 port options to add devices like a full-sized keyboard and mouse, an external hard drive, printer, webcam, a speaker set, and more via a single USB-C cable. Connect up to three monitors\* through the Triple Video Dock to expand your visual workspace.


## Triple 4K Ultra-HD Monitor Setup

Enjoy the remarkable visual experience of 4K Ultra HD (UHD), at four times the resolution of standard HD. The Dock supports impressive, Cinema 4K quality on a single DisplayPort monitor to 4096 x 2160 @60Hz for enhanced enjoyment while watching videos, playing games, working and creating. Attach dual 4K UHD DisplayPort screens and add a third 4K UHD HDMI display for crystal clear images and video quality to 3840 x 2160 @60Hz across all three.

- Dock and expand your USB-C laptop with 11 port options
- Connect up to 3 HD 4K displays via 2 DisplayPorts, 1 HDMI port\*
- Keep your laptop charged with up to 60W Power Delivery
- 2x DisplayPort++ 1.2 ports support dual displays to 4K @ 60Hz
- 1x HDMI port with DP Alt Mode supports HD display to 4K @ 30Hz
- 1x USB-C port offers fast data transfer rates to 5Gbps
- 2x USB 3.0 ports with one BC1.2 fast charging port
- 2x USB 2.0 ports; 1x Gigabit Ethernet port
- 2x 3.5mm audio ports for a headphone and microphone
- TAA Compliant

\* Requires installation of DisplayLink driver





## Requirements

## Package Contents

### Host device requirements

- USB-C 3.2 or 4.0(Thunderbolt 3 compatible) device with DP Alt Mode Support
- USB-C with USB mode can only support up to 2 monitors

- 1 x GUD3C11
- 1 x 120W AC power adapter
- 1 x 3.3ft USB Type-C to Type-C cable
- 1 x Driver CD
- 1 x Quick Start Guide
- 1 x Warranty card

### OS requirements

- Windows 7/8/8.1/10
- Mac OS X 10.10+
- Chrome OS
- Ubuntu
- DisplayLink Driver installation (<http://www.displaylink.com/downloads>)
- Host computer USB-C port must support USB Power Delivery 2.0 for charging function

Notes for M1 Mac Users: For M1 Mac Users, please check DisplayLink website for latest Mac Displaylink driver: <http://www.displaylink.com/downloads/macos>

## Specifications

Function	GUD3C11	Dimensions	GUD3C11
<b>Upstream Port</b>		<b>Unit Dimensions</b>	
USB-C	USB 3.1 Gen 1 5Gbps, with Power Delivery up to 60W	Height	3.54" (9cm)
<b>Downstream Port</b>		Depth	1.18" (3cm)
Audio In	1x 3.5mm audio port	Length	8.86" (22.5cm)
Audio Out	1x 3.5mm audio port	<b>Inner Pack</b>	
DisplayPort	2x DisplayPort with up to 4K@60Hz (3840x2160)	Width	10.39" (26.4cm)
Ethernet	1x Gigabit Ethernet	Height	12.8" (32.5cm)
HDMI	1x HDMI with DP Alt Mode, supports up to 4K@30hz (3840x2160)	Length	12.8" (32.5cm)
USB-A	2x USB 3.0; 2x USB 2.0	Inner Pack Qty.	3
USB-C	1x USB 3.1 Gen 1	<b>Unit Package Dimensions</b>	
<b>Power Adapter</b>	External 120W AC Adapter	Width	5.31" (13.5cm)
<b>Operating System Requirements</b>		Height	3.27" (8.3cm)
Mac	Mac OS X 10.10+ ~ 10.13.3	Length	12.6" (32cm)
Windows	Windows 7 / 8 / 8.1 / 10	<b>Master Carton</b>	
<b>Environment</b>		Width	13.78"
Humidity		Height	11.22"
Operation Temperature		Depth	12.6"
<b>Power</b>		Master Carton Qty.	6
Power Delivery Pass-Thru	Power Delivery Pass-through up to 60W	<b>Weight</b>	
<b>Protocols</b>		Master Carton Wt.	19.47lb (8.83kg)
	HDCP 2.2, DisplayPort Alt Mode	Inner Pack Wt.	9.06lb (4.11kg)
		Unit Pack Wt.	2.6lb (1.18kg)
		Unit Wt.	0.8lb (0.36kg)