

GUD4C8K3

Dock Pro USB4 8K Triple View



- 2x HDMI up to 4K@60Hz
- 2x Displayport up to 8K@30Hz
- 2x USB4 full feature ports, up to 8K@30Hz
- 1x USB-C 3.2 Gen 2 (10Gpbs)
 - Supports PD 3.0 max 30W output for mobile charging
- 2x USB-A 3.2 Gen 2 (10Gbps)
- 1x USB-A 3.2 Gen 1 (5Gbps)

- 2x HDMI up to 4K@60Hz
- 2x Displayport up to 8K@30Hz
- 2x USB4 full feature ports, up to 8K@30Hz
- 1x USB-C 3.2 Gen 2 (10Gpbs)
 - Supports PD 3.0 max 30W output for mobile charging
- 2x USB-A 3.2 Gen 2 (10Gbps)
- 1x USB-A 3.2 Gen 1 (5Gbps)
- 1x SD/Micro SD up to 312 Mbps

- 1x 2.5G Ethernet port
- 1x 3.5mm Audio Combo port
- Features Goshen Ridge Controller, this supports Thunderbolt 4 at max bandwidth (40Gbps)
- Supports 8K@30hz in Single View, 4K@60hz in Dual View, 2x 4K@60hz 1x 4K@30hz in Triple View
- Power Delivery up to 96W



Requirements

Host device requirements

- USB4 or Thunderbolt 4 host required for max bandwidth (40Gbps)
- USB-C(DP alt mode) and Thunderbolt 3 hosts are compatible at lower bandwidth

OS requirements

- Windows 10,11
- Mac OS X 10.13+

Package Contents

- 1x GUD4C8K3
- 1x USB4 C to C cable (.08m)
- 1x Power Adapter
- 1x QSG
- 1x Warranty Card

Specifications

Function	GUD4C8K3	Dimensions	GUD4C8K3
Upstream Port		Unit Dimensions	
USB-C	USB4 Type-C for Host (40Gbps)	Height	0.7" (1.8 cm)
Downstream Port		Length	8.8" (22.5 cm)
Audio	1x 3.5mm Audio Combo port	Width	3.3" (8.5 cm)
USB-A	2x USB-A 3.2 Gen 2 (10Gbps) 1x USB-A 3.2 Gen 1 (5Gbps)	Unit Package Dimensions	
USB-C	1x USB 3.2 Gen 2 (10Gbps) 2x USB4 full feature (40Gbps) up to 8K@30hz	Height	2.5" (6.5 cm)
Card Reader	1x SD 1x Micro SD/TF Max 312 mbps	Length	9.64" (24.5 cm)
Ethernet	1x RJ45 10/100/1000/2.5G bandwidth	Width	4.3" (11 cm)
HDMI	2x HDMI up to 8K@30hz	Master Carton	
DisplayPort	2x Displayport up to 8K@30hz	Height	
Power Adapter	DC 20V 150W Power supply	Length	
Power		Width	
Output Rating	PD 3.0 up to 96W	Master Carton Qty.	
		Weight	
		Unit Pack Wt.	
		Unit Wt.	0.9 lbs (0.4 kgs)