

GUH227

7- Port Hi-Speed USB 2.0 Hub



IOGEAR's 7-port USB 2.0 hub provides 7 Hi-Speed USB 2.0 ports for your high-speed connectivity needs. This device is fully compliant to USB 2.0 specifications and provides a data transfer rate of up to 480 Mbps. It supports Windows XP, Vista, 7, 8, 8.1 and Mac OS X 10.2 or later. The MiniHub™ also supports USB 1.1 devices since it is backward compatible with USB 1.1 specifications. It is very easy to use, Plug-n-Play, hot swappable and portable. It is backed by IOGEAR's 3 Year Limited Warranty.

- 7 USB 2.0 ports for easy expansion
- Supports data transfer rate of up to 480 Mbps
- Removable stand allows horizontal or vertical use
- 40 times faster than USB 1.1 products
- connect up to 127 devices together (through daisy chaining)
- Plug-n-Play, hot swappable
- Automatically switches to the highest speed supported by peripheral
- Backward compatible with USB 1.1 specifications
- Supports Windows XP, Vista, 7, 8, 8.1 and Mac OS X or later version
- 3 Year Limited Warranty



Requirements

For PC Users

- Windows XP, Windows Vista, Windows 7, Windows 8/8.1, 10
 - Available USB 2.0 port
 - Chrome Book
 - Linux®, Unix and other USB supported systems*
- *Additional drivers and support may be needed

For MAC Users

- Mac 8.6 or greater. Requires OS X for USB 2.0 support
- Available USB 2.0 port

Package Contents

- 1 x GUH227 - Hi-Speed USB 2.0 Hub
- 1 x Power Adapter
- 1 x USB A to B Cable (6')
- 1 x Quick Start Guide
- 1 x Warranty Card
- 1 x Vertical Stand

Specifications

Function	GUH227	Dimensions	GUH227
Housing		Unit Dimensions	
Case	Plastic	Height	5.9 in. (15 cm.)
Power Consumption	5.0V - 3A	Depth	1.18 in. (3 cm.)
Ports	7 downstream, 1 upstream	Width	3.42 in. (8.7 cm.)
Operating Temperature	20 to 50 degrees (Celsius)	Inner Pack	
Storage Temperature	0 to 70 degrees (Celsius)	Height	7.63" (19.38cm)
Operating System Support	Windows®, 98SE, 2000, ME, XP, MAC OS 8.6 or greater	Length	9.25" (23.49cm)
USB Specification	USB 1.1 and 2.0 compliant	Width	16.5" (41.91cm)
Transfer Rate	480 Mbps	Inner Pack Qty.	6
Humidity	20-80% RH, (Non Condensing)	Unit Package Dimensions	
Cable Length	6 ft. (1.83 m.)	Height	9.75" (24.77cm)
Power Connections	DC adapter (included)	Width	7" (17.78cm)
Connectors (Input)	USB Type A	Depth	2.63" (6.68cm)
LEDs		Master Carton	
ACT (Activity)	7	Height	16.25" (41.28cm)
Connectors (Computer)	USB Type B	Width	17.5" (44.45cm)
		Depth	9.75" (24.77cm)
		Master Carton Qty.	12
		Weight	
		Master Carton Wt.	15.95lb (7.25kg)
		Inner Pack Wt.	7.40lb (3.36kg)
		Unit Pack Wt.	1.15lb (0.52kg)
		Unit Wt.	0.34lb (0.154kg)