

GUH274

4-Port USB 2.0 MicroHub™



IOGEAR's 4-Port USB 2.0 Hub provides 4 Hi-Speed USB 2.0 ports for your high-speed connectivity needs. This device is USB 2.0 certified and provides a data transfer rate of up to 480 Mbps (high speed). It supports Windows 98SE, 2000, ME, XP, Vista, Windows 7, Windows 8/8.1 and Mac OS X or later. The MicroHub™ 2.0 also supports USB 1.1 devices since it is backward compatible with USB 1.1 specifications. It is very easy to use, Plug-n-Play, hot swappable and portable. It is backed by IOGEAR's 3 Year Limited Warranty.

Declaration of Conformity

- 4 USB 2.0 ports for easy expansion
- Built-in USB cable for immediate connection
- Tuck-away cable design eliminates cable clutter
- Supports a data transfer rate of up to 480Mbps
- 40 Times faster than USB 1.1 products
- Guarantees 12Mbps bandwidth to each port for USB 1.1 devices
- Plug-n-Play, hot swappable
- Backward compatible with USB 1.1 specifications
- Supports Windows 98SE, 2000, ME, XP, Vista, 7, 8, 8.1 and Mac OS X or later version
- Overcurrent Protection
- LEDs allow for easy status monitoring
- 3 Year Limited Warranty









Requirements

For PC Users

- Windows 8/8.1, 10, 11
- Available USB 2.0 port
- Chrome Book
- Linux®, Unix and other USB supported systems*
- *Additional drivers and support may be needed

For MAC Users

• Mac OS X 10.15 or later

Package Contents

- GUH274 Hi-Speed USB 2.0 Hub
- Manual
- Power Adapter
- Warranty / Registration Card

Function	GUH274	Dimensions	GUH274
Housing		Unit Dimensions	
Case	Plastic	Height	0.5 in. (1.20 cm.)
LEDs		Length	3.5 in. (9.00 cm.)
Power On	1	Width	1.5 in. (3.85 cm.)
Power Consumption	5.0V,	Unit Package Dimensions	
Ports	4 downstream	Height	4.5 in.
Operating Temperature	20 to 50 degrees (Celsius)	Width	1.875 in.
Storage Temperature	0 to 70 degrees (Celsius)	Depth	7.675 in.
Operating System Support	Windows®, 98SE, 2000, ME, XP, MAC OS 8.6 or greater	Master Carton	
USB Specification	USB 1.1 and 2.0 compliant	Height	10.5 in.
Transfer Rate	480 Mbps	Width	13.125 in.
Humidity	20-80% RH, (Non Condensing)	Depth	15.125 in.
Cable Length	2.0 in. (5.0 cm.)	Master Carton Qty.	24
Power Connections	DC adapter (included)	Weight Master Carton Wt.	4471
Cable Connections		Master Carton Wt. Unit Pack Wt.	14.7 lb.
Input	Hi-Speed USB Type A (female)	Unit Wt.	0.5 lb. 0.1 lbs. (0.04 kg.)