

GUH275

4-Port USB 2.0 Hub



IOGEAR's 4-port USB 2.0 hub provides 4 Hi-Speed USB 2.0 ports for your high-speed connectivity needs. This device is USB 2.0 and provides a data transfer rate of up to 480 Mbps (high speed). The GUH275 is an updated, portable version of IOGEAR's first USB 2.0 hub, this updated version features a smaller form factor and uses an industry standard hub chip supporting the 480Mbps bandwidth to each device. It supports Windows® 98SE, 2000, ME, XP, and Mac OS X or later. The MicroHub™ 2.0 also supports USB 1.1 devices since it is backward compatible with USB 1.1 specifications. It is very easy to use, Plug-n-Play, hot swappable and portable. It is backed by IOGEAR's 3 Year Limited Warranty.

- 4 USB 2.0 ports for easy expansion
- Supports a data transfer rate of up to 480 Mbps
- 40 Times faster than USB 1.1 products
- Plug-n-Play, hot swappable
- Backward compatible with USB 1.1 specifications
- Supports Windows 98, 98SE, 2000, ME, XP, and Mac OS X or later version
- Overcurrent Protection
- LED light for status monitoring
- Self Powered (also available: optional power port)
- USB cable tucks away when not in use
- 3 Year Limited Warranty



Requirements

For PC Users

- Windows® 98SE, 2000, ME, XP
- Available USB 2.0 port

For MAC Users

- Mac 8.6 or greater. Requires OS X for USB 2.0 support
- Available USB 2.0 port

Note: Optional power adapter IOGEAR model #0AD8-0705-261 (100-240V, DC5V 2.6A) may be required for use with power hungry devices such as external hard drives.

Package Contents

- GUH275 - Hi-Speed 4-port USB 2.0 Hub

Specifications

Function	GUH275	Dimensions	GUH275
Housing		Unit Dimensions	
Case	Plastic	Height	0.5 in. (1.27 cm.)
Power Consumption	5.0V	Length	3.5 in. (8.89 cm.)
Ports	4 downstream	Width	1.5 in. (3.80 cm.)
Operating Temperature	20 to 50 degrees (Celsius)	Unit Package Dimensions	
Storage Temperature	0 to 70 degrees (Celsius)	Height	0.75 in. (1.90 cm.)
Operating System Support	Windows®, 98SE, 2000, ME, XP, MAC OS 8.6 or greater	Width	4.10 in. (10.41 cm.)
USB Specification	USB 1.1 and 2.0 compliant	Depth	6.25 in. (15.87 cm.)
Transfer Rate	480 Mbps	Master Carton	
Humidity	20-80% RH, (Non Condensing)	Height	14.0 in. (350 mm.)
Cable Length	2.0 in. (5.0 cm.)	Width	8.48 in. (212 mm.)
Power Connections	Optional DC adapter port for optional power adapter.	Depth	9.4 in. (235 mm.)
		Master Carton Qty.	40
		Weight	
		Master Carton Wt.	7.9 lbs. (3.6 Kg.)
		Unit Pack Wt.	0.14 lbs. (.063 Kg.)
		Unit Wt.	0.10 lbs. (.045 Kg.)