

GUH276

3-Port USB 2.0 Mobile Hub



Charge & Sync*

The IOGEAR Mobile Hub is a hybrid 3-Port USB 2.0 Hub and Mini-USB charging cable. It provides three High-Speed USB 2.0 ports with tuck-away cable design. The extra room between ports ensures no single port will be blocked. In addition to three USB 2.0 USB ports, the IOGEAR Mobile Hub comes with one built-in 5-pin Mini-B USB connector for easier connection to any Mini-B USB device. The connector is designed for both data transfer and power charging for devices supporting Mini-B USB charging to eliminate cable clutter. Compact and lightweight, the IOGEAR Mobile Hub is stylish and functional. The tuck-away USB cable design avoids cable clutter and makes the hub easy to carry and convenient to store.

*Your mobile device must have the mini-B USB connector built-in, and allow charging and/or synchorizating through the mini-B USB connection

- 2-in-1 Hub + Mini-B USB connector design
- Tuck-away cable management for convenient storage
- Lightweight and no power supply required*

- Easy connection to cell phone or other USB devices with Mini-B connector
- * Total device power consumption cannot be greater than 350 mA.









How does it work?

Three High-Speed USB 2.0 ports with data transfer speeds of up to 480Mbps. Extra room between ports ensuring no single port will be blocked.

Easy connection to cell phones or other mini-USB devices. Charge and sync your mobile devices with less cable clutter.



USB Mini-B



USB Type A



Requirements

Package Contents

Windows 2000, XP, Vista & 71 x 3+1 port USB 2.0 Hub

Mac OS X v10.3.9 or later 1 x Warranty Card

Specifications

Function	GUH276	Dimensions	GUH276
USB Specification	USB 2.0	POP Information	
Power		10" Peg Hook	12 pcs
Amps	Total device power consumption up to 350mAh	6" Peg Hook	8 pcs
Voltage	Total device power consumption up to 5V	Unit Dimensions	
Humidity	20 ~ 80% RH, (Non Condensing)	Width	1.97 in. (5 cm)
Storage Temperature	32 ~ 158 degree Fahrenheit (0 ~ 70 degree Celsius)	Height	0.71 in. (1.8 cm)
		Length	3.58 in. (9.1 cm)
Operating Temperature	68 ~ 122 degree Fahrenheit (20 ~ 50 degree Celsius)	Unit Package Dimensions	
Computer Interface	USB	Width	4.8 in. (12.2 cm)
		Height	7.6 in. (19.3 cm)
		Depth	1.1 in. (2.8 cm)
		Master Carton	
		Width	16.1 in. (40.8 cm)
		Height	11.02 in. (28 cm)
		Depth	5.79 in. (14.7 cm)
		Master Carton Qty.	24
		Weight	
		Master Carton Wt.	5.6 lb (2.54 kg)
		Unit Pack Wt.	0.2 lb (0.09 kg)
		Unit Wt.	0.1 lb (0.045 kg)